



- Instrumentation cables 250 V
- Overall Screen (OS)
- **Hydrocarbons resistant**

STANDARDS

Ensayo IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cables are used to transmit analogue or digital signals in measurement and process control where hydrocarbons may be present.

Nexans code

- 1st serie = number of pairs, triples or quads: 01 to 27
- 2nd serie = pair (IP), triple (IT), quad (IQ)
- 3rd serie = conductor 05 (1 x 0.8 mm), 09 (7 x 0.4 mm) or 15 (7 x 0.52 mm)
- 4th serie = overall screen (EG), individual screen + overall screen (EI)
- 5th serie = mechanical protection: without metal tape (SF), with steel tape (FA), with lead and steel tape (PF)

Design

Conductor:

- Solid plain copper 0.50 mm² (1 x 0.80 mm) or stranded plain copper cross-section 0.88 mm² (7 x 0.40 mm) or 1.5 mm² (7 x 0.52 mm)

Insulation:

- Polyvinyl chloride (PVC)

Overall screen:

- Polyester tape
- Tinned copper drain wire
- Aluminium/polyester tape

Outer sheath:

- Polyvinyl chloride (PVC)
- Colour: light-blue or grey

Core identification

- Pair: natural - red
- Triple: natural - red - blue
- Quad: natural - red - blue - yellow
- Natural cores printed with pair/triple number

Marking

NEXANS 279 - Number of pair/triple/quad IP/IT/IQ 05/09/15 EG SF IEC 60332-3-22(A) + metric marking

CONTACT

Market information
 industryprojects.business@lynxéo
 group.com



No propagador del incendio
 EN IEC 60332-3-22 (cat A)



Resistencia química
 Hydrocarbons resistant



Resistencia a interferencias electromagnéticas
 Sí



Temp. ambiente de utilización
 -20 ... 60 °C



Max.conductor temp.in service
 70 °C

CHARACTERISTICS

Características de construcción

Material del conductor	Plain copper
Aislamiento	PVC
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Cubierta exterior	PVC

Características dimensionales

Sección del conductor	0,5 mm ²
Número de pares	12
Number of triples	-
Número de cuadretes	-
Diámetro del conductor	0,8 mm
Diámetro sobre aislamiento	1,6 mm
Diámetro exterior mínimo	13,4 mm
Diámetro exterior máximo	14,9 mm
Peso aproximado	255 kg/km

Características eléctricas

Tensión de operación	250 V
----------------------	-------

Características de uso

No propagador del incendio	EN IEC 60332-3-22 (cat A)
Resistencia química	Hydrocarbons resistant
Resistencia a interferencias electromagnéticas	Sí
Temperatura ambiente de utilización (rango)	-20 ... 60 °C
Temperatura máxima del conductor	70 °C
Standard	NFM

ELECTRICAL DATA NF M 87202

Electrical data

Section	Maximum Voltage (V)	Voltage Test (V)	DC Lineic resistance at 20°C (Ω/km)	Self Inductance mH/km		Capacitance between cond. (nF/km)
				Non Armoured	Armoured	
05	250	2 000	37.5	0.33	0.38	≤145
09	250	2 000	21.4	0.31	0.36	≤160
15	250	2 000	12.1	0.31	0.36	≤180



No propagador del incendio
EN IEC 60332-3-22 (cat A)



Resistencia química
Hydrocarbons resistant



Resistencia a interferencias electromagnéticas
Sí



Temp. ambiente de utilización
-20 ... 60 °C



Max. conductor temp. in service
70 °C

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations



No propagador del incendio
EN IEC 60332-3-22 (cat A)



Resistencia química
Hydrocarbons resistant



Resistencia a interferencias electromagnéticas
Sí



Temp. ambiente de utilización
-20 ... 60 °C



Max.conductor temp.in service
70 °C