

MULTICORE SENSOR CABLES FOR DRAG CHAIN APPLICATION ADVANCED

HOME RUN CABLES FOR DRAG CHAIN APPLICATION ADVANCED 8x0,34 +3x1,0



Home run cables for very dynamic applications MOTIONLINE® ADVANCED

STANDARDS

Product UL and CSA approval

Home run cables for very dynamic applications; PUR Jacket; resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

CONTACT

Market information
industryprojects.business@lynxeogroup.com



Halogen free
Yes



Operating temp.
 - °C



Storage temperature, range
 -40 ... 80 °C



Flame retardant
 IEC 60332-1-2; UL 1581 FT1



Oil resistance
 DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

Construction characteristics

Construction type	-
Conductor material	Bending-resistant conductor with bare copper wires
Insulation	TPM with very low capacitance
Lay Up	-
Insulation colour	-
Outer sheath	-
Sheath colour	-
Halogen free	Yes

Dimensional characteristics

Outer Diameter	- mm
Copper content	- kg/km
Approximate weight	- kg/km

Electrical characteristics

Rated Voltage U ₀ /U	300 V
Test voltage	2000 V

Mechanical characteristics

Bending cycles	- Mio.
Speed	-
Maximum acceleration	- m/s ²

Usage characteristics

Field of application	-
Minimum dynamic operating bending radius	- (xD)
Operating temperature, range	- °C
Storage temperature, range	-40 ... 80 °C
Flame retardant	IEC 60332-1-2; UL 1581 FT1
Oil resistance	DIN EN 50363-10-2 & DIN EN 60811-404