



Country Ref.: Etude 132836

### CONTACT

Market information  
[industryprojects.business@lynxogroup.com](mailto:industryprojects.business@lynxogroup.com)

#### International Designation:

4 x 40 AWG wires

Medical Video Endoscopy cable

### STANDARDS

Product Nexans specification

#### Characteristics

Very flexible cable with an extremely good mechanical behaviour.  
 Withstands miscellaneous sterilisation process.

#### CONSTRUCTION

##### 1- CORE (A)

AWG 40 stranded silver plated alloy conductor.  
 Nominal diameter : 0.09 mm.  
 MFA insulation.  
 Diameter : 0.20 +/- 0.02 mm.

4 Cores A twisted  
 Nominal diameter : 0.48 mm.

##### 2- SHIELD

AWG 44 silver plated copper braid.  
 95% coverage.  
 Nominal diameter : 0.75 mm.

##### 6- FEP Jacket

Diameter : 0.95 +/- 0.10 mm.

#### Main Characteristics

Minimum static bending radius : 5 x Overall diameter.



Cable flexibility  
**Very flexible**



Maximum operating temperature  
**150 °C**



Minimum operating temperature  
**-30 °C**

**CHARACTERISTICS****Construction characteristics**

Conductor material	Silvered copper
Conductor shape	Multi stranded
Construction type	Shielded and sheathed
Insulation	PFA

**Dimensional characteristics**

Wire diameter	- mm
Outer Diameter	0.95 mm
Maximum outer diameter	1.05 mm
Approximate weight	2.11 g/m

**Electrical characteristics**

Operating voltage	24 V
-------------------	------

**Mechanical characteristics**

Cable flexibility	Very flexible
-------------------	---------------

**Usage characteristics**

Maximum operating temperature	150 °C
Minimum operating temperature	-30 °C
Mechanical Resistance	Good mechanical resistance