



CONTACT

Market information
industryprojects.business@lynxéo
ogroup.com

Torsion resistant low-voltage cable for free hanging of max. 100 m

STANDARDS

Produit EN 50363; HD 22-13; IEC 60228; IEC 60502

APPLICATIONS

Low-voltage loop cable WINDLINK LV-RS (N)HXCSLOE was developed for special application condition in wind turbines. The construction is torsion resistant by free hanging of max.100 m. These cables are specified for medium mechanical stress and for operation under permanent influence of sea water and usage outdoor.

Resistance to

- permanent movement
- permanent vibrations
- compressive stress
- oil, EN60811-2-1, ASTM No.2, 24 h at 100 °C
- low smoke, IEC 61034, >50 %
- halogen-free IEC 60754
- permanent influence of seawater
- ozone influence, EN 60811-2-1 clause 8
- suitable for torsion of max. 6 counterclockwise rotations and min. free hanging up from 25 m

Design

Core

Conductor

- Copper, plain, flexible concentrically stranded circular

Insulation

- Extruded halogen-free rubber compound EI8 acc. to EN 50363-5

Screen

- Tinned wire copper braid, covering min. 80 %

Outer Sheath

- Extruded halogen-free EVA compound EM8 acc. to EN 50363-6

CHARACTERISTICS

Caractéristiques de construction

Sans halogène	IEC 60754-2
---------------	-------------

Caractéristiques électriques

Tension de service nominale Uo/U (Um)	0,6 / 1 kV
---------------------------------------	------------

Caractéristiques d'utilisation

Non propagateur de la flamme	EN 50265-2-1
Sans silicone	Oui
Conforme RoHS	Oui
Température maximale sur l'âme	90 °C
Résistance aux intempéries	Excellente
Température maximale sur l'âme en court circuit	250 °C

PRODUCT LIST

Reference	Country Ref.	Name
☎ 71320700	-	(N)HXCSLOE-JZ 4x1,5
☎ 71320701	-	(N)HXCSLOE-JZ 4x4
☎ 71320702	-	(N)HXCSLOE-JZ 12x1,5
☎ 71320703	-	(N)HXCSLOE-JZ 25x1
☎ 71320704	-	(N)HXCSLOE-JZ 32x1,5
☎ 713207..	-	(N)HXCSLOE-JZ 42x1,5
☎ 71320708	-	(N)HXCSLOE-JZ 12x2,5
☎ 71320706	-	(N)HXCSLOE-JZ 25x0,75
☎ 71320707	-	(N)HXCSLOE-JZ 5x2,5
☎	71320714	WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV
☎	-	WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV
☎ 71320728	-	WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV
☎	71320717	WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV

☎ = Make to order, ☎ = In stock,

SELLING AND DELIVERY INFORMATION

Inkjet marking e.g.: WINDLINK LV-RS (N)HXCSLOE 0.6/1 kV | NEXANS I