



- Instrumentation cables 170/300 V
- With lead cover (LC)
- Individual & Overall Screen (IOS)
- Aliphatic and aromatic hydrocarbons resistant

## STANDARDS

Test IEC 60331; IEC 60332-3-22 Cat. A

## APPLICATIONS

These instrumentation and communication cables are used to transmit analogue or digital signals in measurement and process control. They are well adapted to underground use in industrial applications, in moist areas, where hydrocarbon and mechanical protection are needed. The lead cover brings an enhanced resistance to aromatics hydrocarbons. The individual screening of each pair limits the consequence of crosstalk. They maintain circuit integrity when exposed to fire.

## Design

### Conductor:

Stranded bare copper class 2

### Insulation:

Silicone rubber (SiI)

### Individual screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

Polyester tape

### Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium backed polyester tape

### Inner sheath:

Low Smoke Zero Halogen (LSZH)

Colour: black

### Lead sheath:

### Bedding (intermediate sheath):

Polyvinyl chloride (PVC)  
Colour: black

耐火  
IEC  
Armour:  
Galvanized steel wires (SWA)

阻燃  
EN IEC 60332-3-22  
(cat A)

耐化学物质  
Aliphatic and  
aromatic  
hydrocarbons  
(SWA)



抗电磁干扰  
是



操作温度  
-20 ... 60 ° C



芯线最高静止温度  
90 ° C

## CONTACT

Market information  
industryprojects.business@lyn  
xeogroup.com



额定电压U<sub>0</sub>/U  
170/300V



机械耐冲击性能  
好

## CHARACTERISTICS

### 结构特性

导体材料	裸铜线
导体类型	Stranded, class 2
绝缘	硅树脂橡胶
线对屏蔽	Tinned copper drain wire + aluminium/polyester tape
总屏蔽	Tinned copper drain wire + aluminium/polyester tape
内护套	Low smoke, zero halogen thermoplastic compound
Lead Sheath	Yes
中间护套	PVC
铠装类型	镀锌钢丝
外护套	聚氯乙烯
防护	Yes

### 电气特性

额定电压U <sub>0</sub> /U	170/300V
-----------------------	----------

### 机械特性

机械耐冲击性能	好
---------	---

### 使用特性

耐火	IEC 60331
阻燃	EN IEC 60332-3-22 (cat A)
耐化学物质	Aliphatic and aromatic hydrocarbons resistant
抗电磁干扰	是
操作温度范围	-20 ... 60 ° C
芯线最高静止温度	90 ° C
标准	EN

## SECTION 0.5MM<sup>2</sup>

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10135231	2	0.9	2.06	10.1	12.1	14.1	15.9	17.4	20.2	895
	5	0.9	2.06	13.2	15.2	17.2	19.7	21.1	24.5	1320
	10	0.9	2.06	17.5	19.7	21.7	24.2	24.8	29.0	1861
10135236	20	0.9	2.06	23.2	25.8	28.2	30.7	31.1	36.2	2810
	30	0.9	2.06	28.2	31	33.4	36.6	36.5	42.6	3916



额定电压U<sub>0</sub>/U  
170/300V



机械耐冲击性能  
好



耐火  
IEC 60331



阻燃  
EN IEC 60332-3-22  
(cat A)



耐化学物质  
Aliphatic and aromatic  
hydrocarbons  
resistant



抗电磁干扰  
是



操作温度  
-20 ... 60 ° C



芯线最高静止温度  
90 ° C

## SECTION 0.75MM<sup>2</sup>

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10135238	2	1.1	2.26	10.8	12.8	14.8	16.6	18.0	21.0	956
	5	1.1	2.26	14.2	16.4	18.4	20.9	22.2	25.8	1481
	10	1.1	2.26	18.9	21.3	23.3	25.8	26.3	30.7	2130
10135243	20	1.1	2.26	24.8	27.4	29.8	33.0	33.1	38.6	3256
	30	1.1	2.26	30.6	33.6	36	39.2	39.1	45.6	4417

## SECTION 1.0MM<sup>2</sup>

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10135245	2	1.28	2.44	11.3	13.3	15.3	17.1	18.5	21.5	1001
	5	1.28	2.44	15.1	17.3	19.3	21.8	23.0	26.8	1595
	10	1.28	2.44	20.2	22.6	24.6	27.1	27.6	32.2	2290
10135250	20	1.28	2.44	26.6	29.4	31.8	35.0	35.1	41.0	3689
	30	1.28	2.44	32.6	35.6	38.4	41.6	41.2	48.1	4870

## SECTION 1.5MM<sup>2</sup>

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
10135252	2	1.5	2.66	12.2	14.2	16.2	18.0	19.5	22.7	1102
	5	1.5	2.66	16.2	18.4	20.4	22.9	24.2	28.1	1749
	10	1.5	2.66	21.8	24.4	26.4	28.9	29.3	34.1	2643
10135257	20	1.5	2.66	29.3	32.3	34.7	37.9	37.9	44.2	4373
	30	1.5	2.66	35.1	38.3	41.1	45.1	44.6	52.0	6033



额定电压U<sub>0</sub>/U  
170/300V



机械耐冲击性能好



耐火  
IEC 60331



阻燃  
EN IEC 60332-3-22  
(cat A)



耐化学物质  
Aliphatic and  
aromatic  
hydrocarbons  
resistant



抗电磁干扰是



操作温度  
-20 ... 60 ° C



芯线最高静止温度  
90 ° C

## SECTION 2.5MM<sup>2</sup>

Reference	nb pairs	Conductor diam. [mm]	Diam. over insulation [mm]	Diam. over inner sheath [mm]	Diameter over lead sheath [mm]	Diam. intermediate sheath [mm]	Diam. over armour [mm]	Min. outer diam. [mm]	Max. outer diam. [mm]	Approx. weight [kg/km]
	2	1.91	3.07	13.7	15.9	17.9	20.4	21.7	25.3	1443
	5	1.91	3.07	18.3	20.7	22.7	25.2	26.3	30.6	2092
	10	1.91	3.07	24.6	27.2	29.6	32.8	32.9	38.4	3336
	20	1.91	3.07	33.1	36.3	39.1	42.3	42.0	49.0	5335
	30	1.91	3.07	40.3	43.9	46.7	50.7	50.0	58.3	7579

## SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) on request.

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



额定电压U<sub>0</sub>/U  
170/300V



机械耐冲击性能好



耐火  
IEC 60331



阻燃  
EN IEC 60332-3-22  
(cat A)



耐化学物质  
Aliphatic and  
aromatic  
hydrocarbons  
resistant



抗电磁干扰是



操作温度  
-20 ... 60 °C



芯线最高静止温度  
90 °C