



CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

Wire and Jacketed Shielded Cable.

Aero engine and high temperature application.

STANDARDS

Product 448-010-3-10

DESIGN CONSTRUCTION

CONDUCTOR

AWG 24, 19 x 0.127 mm

(S = 0.24 mm²)

AWG 22, 19 x 0.16 mm

(S = 0.38 mm²)

Nickel coated high strength copper alloy

INSULATION

Polyimide tape

PTFE tape

SHIELD

Nickel plated copper spiral screen

JACKET

Polyimide Tape

PTFE Tape

IDENTIFICATION

Colour of cores : White - Red - Blue - Yellow - Green

Colour Jacket : Green for AWG 22

: White for AWG 24

Colour of marking : Green

Marking text : " 9310-N££CA**## F0241 ++++ "

££ = Number of Cores

** = AWG

(++++) = Year of manufacturing

= BL (Spiral screen), () Single wire



操作温度
-65 ... 260 ° C



阻燃 - 火焰
FAR/JAR part 25 sec 25.869 (a) (4) Appendix F part 1 (3)



耐油
Very good resistance to aircraft fluids

CHARACTERISTICS

电气特性

工作电压

600 V

最大工作频率

0.002 MHz

使用特性

操作温度范围

-65 ... 260 ° C

阻燃 - 火焰

FAR/JAR part 25 sec 25.869 (a) (4) Appendix F part 1 (3)

耐油

Very good resistance to aircraft fluids

SELLING AND DELIVERY INFORMATION

操作温度
-65 ... 260 ° C阻燃 - 火焰
FAR/JAR part 25 sec 25.869 (a) (4) Appendix F part 1 (3)耐油
Very good resistance to aircraft fluids