



CONTACT

Market information
industryprojects.business@lynxéogroup.com

Fire Resistant Cable, Single and Multi-cores Screened and Jacketed

Aero-engine services applications.

STANDARDS

National ESW 1203; ESW 1202

CORE

Stranded conductor
 Nickel clad copper alloy (ESW 1202)
 Nickel clad copper (ESW 1203)
 004 : 19 x 0.15 mm
 006 : 19 x 0.20 mm
 010 : 19 x 0.25 mm
 012 : 19 x 0.30 mm

INSULATION

Fire resistant insulation
 Polyimide Tape
 PTFE Tape

SCREEN

Nickel plated copper braid

PTFE tape(s)

CHARACTERISTICS

Características eléctricas

Tensión de operación 600 V

Características de uso

Temperatura ambiente de utilización (rango) -65 ... 260 °C

Resistente al fuego -

Resistencia a aceites Very good resistance to aircraft fluids

SELLING AND DELIVERY INFORMATION

CORE IDENTIFICATION :

Single core : White



Temp. ambiente de utilización
 -65 ... 260 °C



Resistente al fuego
 -



Resistencia a aceites
 Very good resistance to aircraft fluids

Two cores : Red - Blue
Three cores : Red - Blue - Yellow
Four cores: Red - Blue - Yellow - Green

JACKET IDENTIFICATION :

White with narrow red stripe

Marking text :

ESW1202-+++ -xxx -FX -FF -**

ESW1203-+++ -xxx -FX -FF -**

+++ = Form code

xxx = Size code

** = Year of production (ie. 14 = 2014)



Temp. ambiente de utilización
-65 ... 260 °C



Resistente al fuego



Resistencia a aceites
Very good resistance to aircraft fluids