



CONTACT

Market information
industryprojects.business@lynxgroup.com

Data bus cable for aeronautic applications. Compatible RS 422

78 Ohms, AWG 24 - Shielded Pair - High temperature

STANDARDS

Product ASNE 0290 XM; EN 3375-006

DESIGN CONSTRUCTION

CORE

AWG 24, 19 x 0.12 mm
 Nickel plated high strength copper alloy
 Fluoropolymer insulation

ASSEMBLY

2 cores twisted

SHIELD

Nickel plated copper braid
 Strand diameter = 0.08 mm
 Coverage ≥ 62 %

JACKET

Polyimide Tapes

CHARACTERISTICS

Usage characteristics

Operating temperature, range	-55 ... 200 °C
Flame retardant	FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)
Oil resistance	Very good resistance to aircraft fluids



Operating temp.
 -55 ... 200 °C



Flame retardant
 FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance
 Very good resistance to aircraft fluids

ELECTRICAL AND HIGH FREQUENCY PERFORMANCES

Voltage rating	: 600 Vrms
Impedance from 1 Mhz to 200 MHz	: $78 \pm 7\Omega$
Mutual capacitance	: 64 pF/m \pm 10%
Maximum attenuation	: 0.035 dB/m at 1 MHz
	: 0.15 dB/m at 10 MHz

IDENTIFICATION

Colour of cores	: Light Blue + Red
Colour of jacket	: Natural
Colour of marking	: Black
Marking tape under jacket	: " - XM 24 FRF "
With	(FR) : Country of origin (FR = France)
	(F) : Manufacturer (F = Filotex)
	(**) : Tear of manufacturing (ie. 14 = 2014)



Operating temp.
-55 ... 200 °C



Flame retardant
FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance
Very good resistance to aircraft fluids