



### CONTACT

Market information  
[industryprojects.business@lynxgroup.com](mailto:industryprojects.business@lynxgroup.com)

Designed for general purpose aircraft wiring applications.

Nickel Platted Aluminium Alloy Conductors  
 UV laser printable.

### STANDARDS

Product ABS 0958; ABS 0949 AD

Test prEN 3475

### DESIGN CONSTRUCTION

#### CONDUCTOR

Nickel plated aluminium rope - lay conductor

#### INSULATION

High performance polyimide tape  
 Special UV PTFE tape

### IDENTIFICATION

Standard color: Grey

Color of marking : Blue

Marking text: AD \*\* FR F++

\*\* = AWG

FR = Country of origin (FR = France) F = Manufacturer (F = Lynx<sup>eo</sup>) ++ = Year of production (i.e. 14 = 2014)

## CHARACTERISTICS

Conductor stranding	-
Operating voltage	600 V
Maximal operating frequency	- MHz
操作度范	- 60 ... 180 °C
Oil resistance	Very good resistance to aircraft fluids



Operating temp.  
 -60 ... 180 °C



Oil resistance  
 Very good resistance to aircraft fluids



RoHS compliant  
 Yes

Arc tracking resistant

Yes

RoHS compliant

Yes



Operating temp.  
-60 ... 180 °C



Oil resistance  
Very good resistance to aircraft fluids



RoHS compliant  
Yes