



CONTACT

Market information
industryprojects.business@lynxeogroup.com

Torsion resistant, PUR, screened control cables

STANDARDS

Produit Spécification Nexans

Application

Control cable WINDLINK® Control C-PUR was specifically designed for wind turbines. These cable is used where cold flexibility and torsion resistance are required. It is therefore a suitable connection for electrical equipments in harsh environments.

Product characteristics

- Suitable for torsion up to $\pm 100^\circ/\text{m}$
- Vibration resistant
- Flame retardant according to IEC 60332-1-2
- Oil resistant according to EN 60811-2-1
- Halogen free according to IEC 60754
- Ozone resistant according to EN 60811-2-1 clause 8
- UV resistant according to IEC 60068-2-5 (only with black outer sheath)

Design

Conductor

Bare copper stranded according to IEC 60228 cl. 6

Insulation

Polyolefine compound

Core indication according to DIN VDE 0293

JZ/OZ: black numbered with/without green-yellow ground wire from 3 conductors

Assembly

Center: filler

Conductors twisted in layers + talc + non woven tape

(TP) Conductors twisted in pairs + Polyester tape + Al/polyester tape (Alu outside)

Inner sheath

Polyurethane compound + non woven tape

(TP) without inner sheath

Screen

Tinned copper braid, coverage $85 \pm 5\%$ + non woven tape

Sheath

Polyurethane compound, matt surface, colour black Ral 9005 or grey Ral 7001



Tension de service nominale Uo/U (Um)
300 / 500 V



Température ambiante d'utilisation en dynamique, plage
-30 ... 80 °C



Temp. utilisation statique
-40 ... 80 °C



Conforme RoHS
Oui

CARACTÉRISTIQUES**Caractéristiques électriques**

Tension de service nominale U _o /U (U _m)	300 / 500 V
Tension d'essai	3000 V

Caractéristiques mécaniques

Mechanical stress	15 N/mm ²
-------------------	----------------------

Caractéristiques d'utilisation

Température ambiante d'utilisation en dynamique, plage	-30 ... 80 °C
Température ambiante d'utilisation en statique, plage	-40 ... 80 °C
Minimum bending radius, occasionally moving	15 (xD)
Minimum bending radius, fixed installation	6 (xD)
Conforme RoHS	Oui

PRODUCT LIST

Reference	Name	Diam.ext.nom [mm]	Poids en cuivre [kg/km]	Masse approx. [kg/km]
	Li9Y11YC11Y 24G0.75	16,6	256	460
	Li9YC11Y (TP) 5x2x0.75	11,4	109	184
	Li9Y11YC11Y 18G1.0	16,0	242	433
	Li9Y11YC11Y 21G1.5	19,2	380	659

SELLING AND DELIVERY INFORMATION

Marking e.g.

NEXANS INTERCOND - Week/Year of production - WINDLINK Control C-PUR - 300/500V n x/G yy mm² shielded twist control cable

n: number of conductors

x/G: without/with Yellow/Green conductor

yy: section of conductor

Meter marking