



## CONTACT

Market information  
industryprojects.business@lynx  
ogroup.com

Torsion resistant, PUR, screened control cables

## STANDARDS

**Producto** Especificaciones Nexans

### Application

Control cable WINDLINK® Control C-PUR was specifically designed for wind turbines. These cable is used where cold flexibility and torsion resistance are required. It is therefore a suitable connection for electrical equipments in harsh environments.

### Product characteristics

- Suitable for torsion up to  $\pm 100^\circ/\text{m}$
- Vibration resistant
- Flame retardant according to IEC 60332-1-2
- Oil resistant according to EN 60811-2-1
- Halogen free according to IEC 60754
- Ozone resistant according to EN 60811-2-1 clause 8
- UV resistant according to IEC 60068-2-5 (only with black outer sheath)

### Design

#### Conductor

Bare copper stranded according to IEC 60228 cl. 6

#### Insulation

Polyolefine compound

Core indication according to DIN VDE 0293

JZ/OZ: black numbered with/without green-yellow ground wire from 3 conductors

#### Assembly

Center: filler

Conductors twisted in layers + talc + non woven tape

(TP) Conductors twisted in pairs + Polyester tape + Al/polyester tape (Alu outside)

#### Inner sheath

Polyurethane compound + non woven tape

(TP) without inner sheath

#### Screen

Tinned copper braid, coverage  $85 \pm 5\%$  + non woven tape

#### Sheath

Polyurethane compound, matt surface, colour black Ral 9005 or grey Ral 7001



Tensión nominal de servicio Uo/U  
300/500 V



Ambient dynamic operating temperature, range  
-30 ... 80 °C



Ambient static op. temp  
-40 ... 80 °C



Acorde con normativa RoHS  
Si

**CHARACTERISTICS****Características eléctricas**

Tensión nominal de servicio U <sub>0</sub> /U	300/500 V
Test voltage	3000 V

**Características mecánicas**

Mechanical stress	15 N/mm <sup>2</sup>
-------------------	----------------------

**Características de uso**

Ambient dynamic operating temperature, range	-30 ... 80 °C
Ambient static operating temperature, range	-40 ... 80 °C
Minimum bending radius, occasionally moving	15 (xD)
Minimum bending radius, fixed installation	6 (xD)
Acorde con normativa RoHs	Si

**PRODUCT LIST**

Reference	Name	Diám. nom. exterior [mm]	Contenido de cobre [kg/km]	Peso aprox. [kg/km]
	Li9Y11YC11Y 24G0.75	16,6	256	460
	Li9YC11Y (TP) 5x2x0.75	11,4	109	184
	Li9Y11YC11Y 18G1.0	16,0	242	433
	Li9Y11YC11Y 21G1.5	19,2	380	659

**SELLING AND DELIVERY INFORMATION**

Marking e.g.

NEXANS INTERCOND - Week/Year of production - WINDLINK Control C-PUR - 300/500V n x/G yy mm<sup>2</sup> shielded twist control cable

n: number of conductors

x/G: without/with Yellow/Green conductor

yy: section of conductor

Meter marking