

CONTACT

Market information
industryprojects.business@lynx
ogroup.com

PVC shielded data transmission cables LIYCY with UL approval

UL Style 2464 80°C 300V

STANDARDS

Produit UL 2464

Application

These cable is used for data and signal transmission where high flexibility and oil resistance are required. It is therefore a suitable connection for electrical panels and sensors.

Product characteristics

- Flame retardant according to IEC 60332-1-2 and UL VW-1
- Oil resistant according to EN 60811-2-1
- UV resistant (on request)

Design**Conductor**

Bare copper stranded according to VDE 0295 cl. 5, IEC 60228 cl.5 and UL 1581 Tab. 20.1

Insulation

PVC compound according to UL Style 80°C 300V

Colour code: according to DIN 47100 (with colour repetition from 44 conductors)

Assembly

Conductors twisted in layers + polyester tape

Drain wire

Tinned copper (optional)

Shield

Tinned copper braid, coverage $85 \pm 5\%$

Sheath

PVC compound, oil resistant, flame retardant, according to UL Style 2464 80°C 300V

Colour code: Black Ral 9005 or Grey Ral 7001

CARACTÉRISTIQUES**Caractéristiques de construction**

Structure	-
-----------	---

Caractéristiques dimensionnelles

Nombre de conducteurs	-
Section du conducteur	- mm ²
Diamètre externe nominal (mm)	- mm

Caractéristiques électriques

Tension de service	300 V
Tension d'essai	1500 V
Insulation resistance at 20°C	20 MOhm.km

Caractéristiques d'utilisation

Température ambiante d'utilisation en statique, plage	-30 ... 80 °C
Minimum bending radius, static (XD)	10