

### CONTACT

Market information  
industryprojects.business@lynxe  
ogroup.com

PVC data transmission cables LIYY

### STANDARDS

**Producto** Especificaciones Nexans

#### Application

These cable is used for data and signal transmission where high flexibility is required. It is therefore a suitable connection for electrical panels and sensors.

#### Design

##### Conductor

Bare copper stranded according to VDE 0295 cl. 5 and IEC 60228 cl.5

##### Insulation

PVC compound type T12 according to IEC 50363-3

Colour code: according to DIN 47100 (with colour repetition from 44 conductors)

##### Assembly

Conductors twisted in layers

##### Sheath

PVC compound type TM2 according to IEC 50363-4

Colour code: Grey Ral 7001

**CHARACTERISTICS****Características de construcción**

Construction type	-
-------------------	---

**Características dimensionales**

Número de conductores	-
Sección del conductor	- mm <sup>2</sup>
Diámetro exterior nominal	- mm

**Características eléctricas**

Tensión de operación	300 V
Test voltage	1500 V
Insulation resistance at 20°C	20 MOhm.km

**Características de uso**

Ambient static operating temperature, range	-30 ... 80 °C
No propagación de la llama	IEC 60332-1-2
Minimum bending radius, static (XD)	7,5