



CONTACT

Market information
industryprojects.business@lynxeogroup.com

Measuring systems low voltage cables according to FANUC standard for dynamic applications, shielded, resistant to oils, flame retardant

STANDARDS

Product UL and CSA approval

DESIGN

Insulation colour code

10x2x28AWG:

(White+Blue) (White+Yellow) (White+Green)

(White+Red) (White+Violet) (Brown+Blue)

(Brown+Yellow) (Brown+Green) (Brown+Red)

(Brown+Violet)

Normative references

Oil resistant

IEC 50363 - 4 - 1 (PVC)

IEC 50363 - 10 - 2 (PUR)

Flame retardant

IEC 60332 - 1 - 2

FT1

UL 1581

EN 50265 - 2 - 1



Operating temp.
-20 ... 80 °C



Storage temperature, range
-50 ... 80 °C



IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1

CHARACTERISTICS

10 x 2 x 28 AWG

Insulation colour	Wht+Bl - Wht+Ye - Wht+Gre - Wht+Rd - Wht+Vio - Br+Bl - Br+Ye - Br+Gr - Br+Rd - Br+Vio
Lay Up	Please request detailed data sheet
Taping	Non woven tape
Shielding	80% tinned copper braid coverage
Sheath colour	
Nominal outer diameter	6.0 mm
Copper content	40 kg/km
()	54 kg/km
Rated Voltage Uo/U	30 V 1500 V
Field of application	Dynamic
Minimum dynamic operating bending radius	10 (xD)
操作度范	- 20 ... 80 ° C
Storage temperature, range	- 50 ... 80 ° C

IEC/EN 60332 - 1 - 2; FT1; UL 1581 FT1

PRODUCT LIST

Reference	Country Ref.	Name	Speed	Maximum acceleration [m/s ²]
10554381	13 - MYF28P10R - W1	13 - MYF 10x2x28AWG PVC	120 m/min	5
10554380	13 - MYF28P10P - W1	13 - MYF 10x2x28AWG PUR	180 m/min	7

☎ = Make to order, 📦 = In stock,