



CONTACT

Market information
industryprojects.business@lynxegroup.com

Aeronautic Engine and High Temperature Applications

Fire Resistant - Jacketed, Shielded Twisted pair

STANDARDS

Product Nexans specification

CORE - EN 2346-005N 004 (DWA22) Series

CONDUCTOR

Stranded AWG 22 conductor
 Nickel clad copper alloy

INSULATION

Fireproof insulation
 Polyimide tape
 PTFE tape

ASSEMBLY

2 x EN 2346-005N 004 cores twisted

SEPARATOR

High temperature glass braid

SHIELD

Nickel plated copper braid
 Coverage > 75%

JACKET

PTFE Tapes

CHARACTERISTICS

Electrical characteristics

Operating voltage 600 V

Usage characteristics

Operating temperature, range -65 ... 260 °C

Fire resistant -

Oil resistance Very good resistance to aircraft fluids



Operating temp.
 -65 ... 260 °C



Fire resistant
 -



Oil resistance
 Very good resistance to aircraft fluids

ELECTRICAL PERFORMANCES

Operating frequency	: up to 2000 Hz
Minimum fire resistance within 15 minutes	
Cores to core	: 10 kΩ
Cores to shield	: 10 kΩ
Nominal linear capacitance	
Core to core	: 65 pF/m
Core to shield	: 115 pF/m
Cores to shield	: 200 pF/m
Maximum transfert impedance	
From 100 kHz to 10 MHz	: 40 mΩ/m
From 10 MHz to 100 MHz	: 4 x f in mΩ/m
	<i>With f = frequency in MHz</i>
Indicative values mutual inductance	
At 0.05 MHz	: 0.82 μH/m
At 0.1 MHz	: 0.76 μH/m
At 0.2 MHz	: 0.68 μH/m
At 0.5 MHz	: 0.60 μH/m
At 1 MHz	: 0.58 μH/m
At 2 MHz	: 0.56 μH/m
At 5 MHz	: 0.53 μH/m
At 10 MHz	: 0.50 μH/m
At 20 MHz	: 0.49 μH/m

IDENTIFICATION

Colour of cores	: White with red stripe + White with blue stripe
Marking colour	: Green
Marking text	: " EN DW A 22 FRF ** " (FRF) = Manufacturer (France) (**) = Year of manufacturing
Colour of jacket	: Brown



Operating temp.
-65 ... 260 °C



Fire resistant
-



Oil resistance
Very good resistance to aircraft fluids