



Servo cables with control pair for very dynamic applications MOTIONLINE® ADVANCED

STANDARDS

Product UL and CSA approval

Servo cables with control pair for very dynamic applications; PUR Jacket; screened, resistant to oils and coolants, notch resistant, flame retardant, resistant to hydrolysis and microbes, PVC- and halogen-free.

CONTACT

Market information
 industryprojects.business@lyn
 xeogroup.com



无卤
是



操作温度
-15 ... 80 ° C



存储温度范围
-50 ... 80 ° C



阻燃 - 火焰
IEC 60332-1-2; UL 1581 FT1



耐油
DIN EN 50363-10-2 & DIN EN 60811-404

CHARACTERISTICS

结构特性

结构类型	(4G1.5 + (2x1.5)C)C
导体材料	Bending-resistant conductor with bare copper wires
绝缘	TPM with very low capacitance
绞合	power cores and control pairs stranded with filler
绝缘色	Power: Black - White marking U/L1/C/L+ V/L2 W/L3/D/L- Yellow/ Green; Signal: Black+White
屏蔽	Tinned copper braid, coverage $\geq 85\%$
线对屏蔽	Signal screen: Tinned copper braid, coverage $\geq 85\%$
外护套	PUR
护套颜色	Orange RAL 2003
无卤	是

尺寸特性

外径	- mm
铜含量	- kg/km
近似重量	- kg/km

电气特性

Rated Voltage U ₀ /U	0.6/1 kV
测试电压	4000 V

机械特性

弯曲循环	10 Mio.
速度	180 m/min
Maximum acceleration	20 m/s ²

使用特性

应用类型	动态
最小弯曲半径 - 动态	10 (xD)
操作温度范围	-15 ... 80 °C
存储温度范围	-50 ... 80 °C
阻燃 - 火焰	IEC 60332-1-2; UL 1581 FT1
耐油	DIN EN 50363-10-2 & DIN EN 60811-404