



Measuring systems cables for fixed installation MOTIONLINE®

STANDARDS

Producto UL and CSA approval

For fixed installations; PVC Jacket, screened, resistant to oils and coolants, flame retardant.

CONTACT

Market information
industryprojects.business@lynx
ogroup.com



Temperatura de almacenamiento (rango)
-40 ... 80 °C



No propagación de la llama
IEC 60332-1-2; UL 1581 FT1



Resistencia a aceites
EN 50363-4-1

CHARACTERISTICS

Características de construcción

Construction type	(2x2x0.22)C
Material del conductor	Bending-resistant conductor with tinned copper wires
Aislamiento	TPM with very low capacitance
Insulation colour	1^ Pair: Green+Yellow; 2^ Pair: Pink+Blue
Taping	Copper/Polyester Tape
Pantalla	Tinned copper braid, coverage ≥ 85%
Cubierta exterior	PVC
Color de cubierta	Gris

Características dimensionales

Contenido de cobre	28 kg/km
Peso aproximado	69 kg/km
Diámetro exterior	7 mm

Características eléctricas

Rated Voltage U _o /U	30 V
Test voltage	300 V

Características de uso

Campo de aplicación	Fixed installations
Minimum dynamic operating bending radius	7,5 (xD)
Temperatura de almacenamiento (rango)	-40 ... 80 °C
No propagación de la llama	IEC 60332-1-2; UL 1581 FT1
Resistencia a aceites	EN 50363-4-1

PRODUCT LIST

Reference	Country Ref.	Name
☎ 44479831	-	MEASURING SYSTEM CABLE ACC. TO SIEMENS® 6FX2008-DC00 (DRIVE CLiQ)

☎ = Make to order, 🏠 = In stock,