



CONTACT

Market information
industryprojects.business@lynxeogroup.com

Designed for high frequency interconnections

Product designed according to : NSA935355

CORE

7 x 0.81 mm Strand
 Silver plated copper covered steel
 Diameter = 2.40 mm

INSULATION

Extruded PTFE
 Diameter = 7.25 ± 0.13 mm

SHIELD

Double braid of silver plated copper
 Strand diameter = 0.16 mm

JACKET

PTFE tape(s)

Glass fiber

Diameter = 10.90 ± 0.25 mm
 Max. weight = 270 g/m



Operating temp.
 -90 ... 200 °C



FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)



Oil resistance
 Very good resistance to aircraft fluids



RoHS compliant
 Yes

CHARACTERISTICS

操作度范	- 90 ... 200 ° C
	FAR/JAR part 25 sec 25.869 (a)(4) Appendix F part 1 (3)
Oil resistance	Very good resistance to aircraft fluids
RoHS compliant	Yes

ELECTRICAL CHARACTERISTICS

Operating frequency	: up to 10 GHz
Dielectric strength	: 10 000 V
Operating voltage	: 3700 Vrms max.
Minimum insulation resistance	: 5000 M .km
Characteristic impedance at 200MHz	: 50 ± 2
Maximum linear capacitance	: 105 pF/m
Nominal relative velocity of propagation	: 69%
Maximum conductor ohmic resistance	: 5.68 /km

HIGH FREQUENCY PERFORMANCES

Frequency (MHz)	Mean Attenuation at 20 ° C (dB/100m)
10	2
200	9.5
400	15
3000	52

SELLING AND DELIVERY INFORMATION

Color of Jacket: Brown
Color of marking on the jacket: White

Marking text : " XS FR F ** "

FR = Country of Origin (FR = France)
F = Manufacturer (F = Lynxéo)
** = Year of manufacturing (ie. 17 = 2017)