



### CONTACT

Market information  
[industryprojects.business@lynxeogroup.com](mailto:industryprojects.business@lynxeogroup.com)

180°C Operating Temperature (up to 200°C Peak)  
 Flexible Nickel Plated Aluminium Light Weight  
 Wires, Single and Multicore Large Sizes

**Designed for general purpose aircraft wiring applications.**

### STANDARDS

International NSA 307110; NSA 935000

### DESIGN CONSTRUCTION

#### SINGLE CORE (ASNE0438 YV)

Product designed according to : ASNE0438

#### CONDUCTOR

A Stranded Conductor  
 Made of Nickel Plated Aluminium

#### INSULATION

Polyimide Tapes

#### EXTERNAL PROTECTION

Aromatic Polyamide Braid  
 Impregnated with a Non Flammable Varnish

#### IDENTIFICATION

By colored threads between polyimide tapes and external braid  
 1, 2 or 3 threads for manufacturer : i.e. Black + Grey = Lynx<sup>eo</sup>  
 2 threads for year of manufacturing : i.e. Black + Pink = 2017

By colored carrier in the external Aromatic Polyamide braid:  
 1 black carrier for wires Size AWG 06, 03, 01, 00 and 0000

Additional identification for multicore (QP):

By colored carrier in the external Aromatic Polyamide braid:

- 1 core with red carrier
- 1 core with blue carrier
- 1 core with yellow carrier

#### Dimensional characteristic note :

YV 000 and YV 0000 products : AWG not defined in ASN specification, values obtained by extension with defined construction.



Betriebstemp.  
 -55 ... 180 °C



Ölbeständig  
 Very good resistance to aircraft fluids

**CHARACTERISTICS****Elektrische Eigenschaften**

Betriebsspannung	600 V
Maximale Betriebsfrequenz	0,002 MHz
Max. Gleichstromwiderstand des Leiters bei 20° C	- Ohm/km

**Anwendungsmerkmale**

Betriebstemperatur	-55 ... 180 °C
Ölbeständig	Very good resistance to aircraft fluids



Betriebstemp.  
-55 ... 180 °C



Ölbeständig  
Very good resistance to aircraft fluids