



CONTACT

Markets and Products Information
rollingstock.business@lynxeogroup.com

COMMUNICATION CABLES

FLAMEX® LLC (Low Loss Coaxial) are intended for antenna wireless communication systems. This product range offers superior RF shielding effectiveness. It is compatible with all standard coaxial connectors.

STANDARDS

Product EN 45545-2 (HL3); EN 50264-1

DESIGN

1. Conductor

Bare Copper

2. Insulation

Foam polyethylene

3. Screen

Aluminium/polyester tape
 Tinned copper braid
 Separator tape

4. Outer sheath

Cross-linked material EM 104 acc. EN 50264-1
 Oil, diesel, ozone and UV resistant
 Colour: black

Example of marking: DTREN 150063 ANTENNA COAXIAL 50 OHMS - LOW LOSS 240 - FLAMEX 239 - EDE 2PM719- week / year - Batch number

ADDITIONAL INFORMATION

- Compatible with all standard coaxial connectors
- Bending radius:
 - Static use: ... x outer cable diameter
 - For installation and occasional movements: ... x outer cable diameter



Halogen free
 EN 60754-1 & EN 60684-2



Flame retardant
 IEC/EN 60332-1-2



Fire retardant
 EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)



Smoke density
 EN/IEC 61034-2



Gases toxicity
 EN 50305-9.2



Electro magnetic interference resistance
 Yes



Chemical resistance
 Good

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Insulation	Foam polyethylene
Taping	Aluminium / Polyester tape
Screen	Tinned copper braid
Separator	Separator Tape
Outer sheath	Cross-linked compound
Halogen free	EN 60754-1 & EN 60684-2

Electrical characteristics

Characteristic impedance	50 Ohm
--------------------------	--------

Usage characteristics

Flame retardant	IEC/EN 60332-1-2
Fire retardant	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
Smoke density	EN/IEC 61034-2
Gases toxicity	EN 50305-9.2
Electro magnetic interference resistance	Yes
Chemical resistance	Good

FLAMEX® LOW LOSS COAXIAL 50 Ω

Reference	Country Ref.	Name	Nom. outer diam. [mm]	Approx. weight [kg/km]	Attenuation, nom. 450 MHz [dB/100m]	Attenuation, nom. 1800 MHz [dB/m]
10275717	2PM719	FLAMEX® LLC 240	6.1	60	17.2	35.9
10275720	2PM720	FLAMEX® LLC 400	10.3	170	8.7	18.2
13117371	2PN366	FLAMEX® LLC 500	12.7	235	6.6	14.5