



CONTACT

Market information
industryprojects.business@lynxéo
ogroup.com

Designed for general Purpose Aircraft Wiring Applications.

UV Laser printable Wire
260°C Operating Temperature Light Weight
Arc Tracking Resistant

STANDARDS

Produkt EN 2267-010

DESIGN CONSTRUCTION

CORE

Stranded Conductor : Nickel Plated High

Strength Copper Alloy (AWG 26 & 24) or
Nickel Plated Copper (AWG 22 to 2)

INSULATION

Special Polyimide Tape
Special UV PTFE Tape(s)

IDENTIFICATION

Standard colour code :

White except AWG 26 which is light yellow and AWG 22 which is light green
AWG 24 is available in light blue color (EN2267-010A 002B)

Color of marking: green

Marking text: EN DR ** FR F ++

DR = Short designation

*** = AWG Wire Size*

FR = Country of origin (FR = France)

F = Manufacturer (F = Lynxéo)

++ = Year of production (i.e. 13 = 2013)

CHARACTERISTICS

Elektrische Eigenschaften

Betriebsspannung Vo DC	28 V
Maximale Betriebsfrequenz	0,002 MHz
Operating voltage between phase and neutral	115 V
Operating voltage between phases	200 V



Betriebstemp.
-55 ... 260 °C

















Ölbeständig
Very good resistance to aircraft fluids

Anwendungsmerkmale

Betriebstemperatur	-55 ... 260 °C
Ölbeständig	Very good resistance to aircraft fluids
Arc tracking resistant	Ja

PRODUCT LIST

	Reference	Country Ref.	Name	Abmessung (AWG)	Max. Kerndurchmesser [mm]	Maximaler Außendurchmesser [mm]
	-	-	EN 2267-010A 001	26	0,49	0,84
	-	-	EN 2267-010A 002	24	0,58	0,96
	-	-	EN 2267-010A 004	22	0,73	1,1
	-	-	EN 2267-010A 006	20	0,97	1,34
	-	-	EN 2267-010A 010	16	1,22	1,61
	-	-	EN 2267-010A 012	18	1,45	1,92
	-	-	EN 2267-010A 020	14	1,73	2,24
	-	-	EN 2267-010A 030	12	2,18	2,7
	-	-	EN 2267-010A 051	10	2,77	3,33
	-	-	EN 2267-010A 090	8	3,85	4,4
	-	-	EN 2267-010A 140	6	5,2	5,7
	-	-	EN 2267-010A 220	4	6,8	7,41
	-	-	EN 2267-010A 340	2	8,6	9,16

☎ = Make to order,  = In stock,Betriebstemp.
-55 ... 260 °CÖlbeständig
Very good resistance to aircraft fluids