



CONTACT

Market information
industryprojects.business@lynxéogroup.com

Outstanding water proof performance

The ENERGYFLEX® WR patented solar cable is designed to withstand humid or immersed installations over its lifetime.

STANDARDS

Produit EN 50618; IEC 60228; IEC 62930

DESIGN

Single core water resistant solar cable with low smoke, halogen free, crosslinked insulation and sheath.

1. Conductor

Stranded tinned copper wires class 5 acc. IEC 60228

2. Insulation

Cross-linked halogen-free rubber
Colour: white

3. Sheath

Cross-linked halogen-free fire retardant rubber
Colour: black

Example of marking: ENERGYFLEX® IWR USE < HAR > H1Z2Z2-K 62930 IEC 131 PV1500-WR 1 x S mm² 1.5/1.5 (1,8) kV DC lynxéo 269 HALOGEN FREE LOW SMOKE Dca

FEATURES

ENERGYFLEX® WR cables are dedicated to the photovoltaic system direct current (D.C.) side with a nominal D.C. voltage of 1.5 kV and a maximum D.C. voltage of 1.8 kV. Cable suitable to be used with Class II equipment.

These cables are suitable for permanent outdoor long-term use, under variable and harsh climate conditions. They are designed and tested to operate at a normal maximum conductor temperature of 90°C and for 20,000 hours up to 120°C. Therefore, the expected period use is 30 to 40 years under normal usage conditions (lifetime acc. to Arrhenius Diagram).

ENERGYFLEX® WR cables have been put under testing protocol TÜV 2PfG 2750/09.20 - Requirements for cables with improved water resistance for installation in photovoltaic-systems 84 days (2,016 hours) / 90°C / 3,6 KV DC (vs 1,8 kV DC at 85°C during 240 hours for IEC 62930 / EN 50618 cables). They are suitable for installations immersed in water for 12 months / year.



Sans halogène
IEC 60754-1



Tension de service nominale Uo/U (Um)
1.0/1.0 (1.2) kV AC
1.5/1.5 (1.8) kV DC



Etanchéité
AD8



Non propagateur de l'incendie
EN 50575



Non propagateur de la flamme
IEC 60332-1-2



Densité de fumée dégagée
IEC 61034-2



Corrosivité des fumées
IEC 60754-2



Résistance aux intempéries
Excellente

CHARACTERISTICS

Caractéristiques de construction

Sans halogène	IEC 60754-1
---------------	-------------

Caractéristiques électriques

Tension de service nominale U _o /U (U _m)	1.0/1.0 (1.2) kV AC 1.5/1.5 (1.8) kV DC
---	---

Caractéristiques d'utilisation

Étanchéité	AD8
Non propagateur de l incendie	EN 50575
Non propagateur de la flamme	IEC 60332-1-2
Densité de fumée dégagée	IEC 61034-2
Corrosivité des fumées	IEC 60754-2
Résistance aux intempéries	Excellente
Tenue à l'ozone	EN 50396
Thermal endurance	IEC 60216-1-2
Température ambiante d'utilisation, plage	-40 ... 90 °C
Température de service maximale	120 °C

DIMENSIONAL CHARACTERISTICS

Section [mm ²]	Diam.nom.cond [mm]	Diam. max. externe [mm]	Masse approx. [kg/km]
4	2,5	6,8	77
6	2,9	7,3	95
10	4	8,2	140

ELECTRICAL CHARACTERISTICS

Section [mm ²]	Max. DC Resist. Cond. 20°C [Ohm/km]	Perm. current rat. air 60°C [A]	Perm. current rating tray 60°C [A]	short circuit conductor 1s [kA]
4	5,09	55	52	0,5
6	5,09	50	67	0,8
10	3,39	98	93	1,4

LIST OF CERTIFICATES

NF EN 50618: BUREAU VERITAS LCIE licence 662568
IEC 62930: BUREAU VERITAS Certificate of conformity 158416-729944
Construction Product Regulation (CPR) Performance: Dca-s2,d2,a1