



CONTACT

Markets and Products Information
rollingstock.business@lynxeogroup.com

COMMUNICATION CABLES

Lynx^{eo} produces a range of optical fiber cables OM3 (50/125 μm) for onboard communication and data transmission. With its halogen-free cross-linked sheathing material the FLAMEX® optical fiber cables conform to the rolling stock requirements.

STANDARDS

Product EN 45545-2 (HL3); EN 50264-1

DESIGN

1. Patch cord

- . Core: glass OM 3 (diameter = 50 μm)
- . Cladding: glass (diameter = 125 ± 3 μm)
- . Coating: acrylate (diameter = 245 ± 10 μm)
- . Buffer: Thermoplastic elastomer (diameter = 900 ± 50 μm)
- . Reinforcement: Aramid yarns
- . Sheath: Cross-linked halogen-free acc. to EN 50264-1 type EM 104 or EM 101 (diameter = 2.00 ± 0.15 mm)

2. Tape (for multi-fibers)

3. Outer sheath

Cross-linked halogen-free acc. to EN 50264-1 type EM 104 or EM101

Example of marking: FLAMEX - Part number - number of fiber x 50/125 - month and year of production

GUIDE TO USE

- Bending radius:
 - Static use: 8 x outer cable diameter
 - For installation and occasional movements: 10 x outer cable diameter



Senza alogeno
EN 60754-1 & EN
60684-2



Ritardante la fiamma
IEC/EN 60332-1-2



Fuoco ritardante
EN IEC 60332-3-24
(cat C); EN IEC
60332-3-25 (EN50305)



Densita' fumo
EN/IEC 61034-2



Tossicita' gas
EN 50305-9.2



Resistenza chimica
Eccellente



Resistenza ad
interferenza
elettromagnetica
SI

CHARACTERISTICS

Caratteristiche costruttive

Tipo fibra	OM3 50/125
Guaina esterna	Mescola reticolata
Senza alogeno	EN 60754-1 & EN 60684-2

Caratteristiche meccaniche

Resistenza allo schiacciamento (IEC 794-1-E3)	250 N/cm
---	----------

Caratteristiche d'utilizzo

Ritardante la fiamma	IEC/EN 60332-1-2
Fuoco ritardante	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
Densita' fumo	EN/IEC 61034-2
Tossicita' gas	EN 50305-9.2
Resistenza chimica	Eccellente
Resistenza ad interferenza elettromagnetica	Si

FLAMEX® OPTICAL FIBER CABLES OM3 50/125

Reference	Country Ref.	Numero di fibre	Diametro esterno [mm]	Peso approssimativo del cavo [kg/km]	Attenuazione, nom. 850 nm (cabled) [dB/1000m]	Attenuazione, nom. 1300 nm [dB/1000m]
	2PH550	2	7	40	3,5	1,5
13117426	2PH551	4	7	40	3,5	1,5
	2PH552	6	8	60	3,5	1,5
	2PH553	8	8,5	80	3,5	1,5