



Reference: 79462520

CONTACTMarkets and Products Information
rollingstock.business@lynxgroup.com**SINGLE CORE POWER CABLES**

FLAMEX® EN 50264 - 3 - 1 1800V M power cables are used for fixed and protected installations. This product range is recommended for narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120 °C conductor temperature is allowed for a 20,000 hours cumulative working time.

STANDARDS

Product EN 50264 - 3 - 1; EN 45545 - HL3; IEC 60228

DESIGN**1. Conductor**

Flexible stranded tinned copper, class 5 acc. to IEC 60228
Optional halogen - free separator tape

2. Insulation

Cross - linked compound type EI 109 acc. to EN 50264 - 1
Oil, diesel, ozone and UV resistant
Colour: black

Example of marking: FLAMEX EN 50264 - 3 - 1 1800 V (mm²) M I
LYNXEO I WW - YYYY

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
 - Static use: 3 x outer cable diameter (5 x D if D > 10mm)
 - For installation and occasional movements: 6 x outer cable diameter

Conductor
flexibility 5Halogen free
EN 60754 - 1 & EN
60684 - 2U_o/U
(Um)
1.8 / 3 (3.6) kV

IEC 60332 - 1 - 2

Fire retardant
EN IEC
60332 - 3 - 24 (cat
C); EN IEC
60332 - 3 - 25
(EN50305)

EN/IEC 61034 - 2

가
EN 50305 - 9.2Operating temp.
- 40 ... 90 °C

CHARACTERISTICS

	Tin plated copper
Conductor flexibility	5
	Cross - linked compound
Halogen free	EN 60754 - 1 & EN 60684 - 2
	4 mm ²
Minimum outer diameter	6.55 mm
Maximum outer diameter	6.85 mm
()	78 kg/km
	- mm
U _o /U (U _m)	1.8 / 3 (3.6) kV
	IEC 60332 - 1 - 2
Fire retardant	EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)
	EN/IEC 61034 - 2
가	EN 50305 - 9.2
操作度范	- 40 ... 90 °C
Max. conductor temperature in service	90 °C
Overload maximum core temperature	- °C
Chemical resistance	Good
Ozone resistance	Yes
U.V resistance	Yes
Short - circuit max. conductor temperature	200 °C