



Reference: 79465203

### CONTACT

Markets and Products Information  
rollingstock.business@lynxeogroup.com

## MULTICORES POWER CABLES

FLAMEX® EN 50264 - 3 - 2 MM multicores power and control cables are used for fixed and protected installations. This product range is recommended for narrow spaces where an optimal bending radius is required. FLAMEX® cables are designed to withstand tough working conditions (oil, ozone, temperature variation, etc.). 120 ° C conductor temperature is allowed for a 20,000 hours cumulative working time.

### STANDARDS

Product EN 50264 - 3 - 2; EN 45545 - HL3; IEC 60228

### DESIGN

1. Conductor  
Flexible stranded tinned copper, class 5 acc. to IEC 60228  
Optional halogen - free separator tape
2. Insulation  
Cross - linked compound type EI 109 acc. to EN 50264 - 1
3. Outer sheath  
Cross - linked compound type EM 104 acc. to EN 50264 - 1  
Oil, diesel, ozone and UV resistant  
Colour: black

Example of marking: FLAMEX EN 50264 - 3 - 2 600V n X (G) ... (mm<sup>2</sup>)  
MM (N)HXSLOE I LYNXEO I WW - YYYY

### GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
  - Static use: 4 x outer cable diameter
  - For installation and occasional movements: 5 x outer cable diameter



Conductor flexibility 5



Halogen free  
EN 60754 - 1 & EN 60684 - 2



Uo/U  
0.6/ 1 (1.2) kV



IEC 60332 - 1 - 2



Fire retardant  
EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)



EN/IEC 61034 - 2



가  
EN 50305 - 9.2



Operating temp.  
- 40 ... 90 ° C

## CHARACTERISTICS

Conductor flexibility	Tin plated copper
	5
Halogen free	Cross - linked compound
	Cross - linked compound
With Green/Yellow core	EN 60754 - 1 & EN 60684 - 2
Minimum outer diameter	3
	1.5 mm <sup>2</sup>
Maximum outer diameter	7.7 mm
( )	8.3 mm
Uo/U (Um)	105 kg/km
	- mm
Fire retardant	0.6/ 1 (1.2) kV
	IEC 60332 - 1 - 2
가	EN IEC 60332 - 3 - 24 (cat C); EN IEC 60332 - 3 - 25 (EN50305)
	EN/IEC 61034 - 2
操作度范	EN 50305 - 9.2
Chemical resistance	- 40 ... 90 ° C
Ozone resistance	Excellent
U.V resistance	Yes
Max. conductor temperature in service	Yes
Short - circuit max. conductor temperature	90 ° C
	200 ° C