



### CONTACT

Market information  
industryprojects.business@lyn  
xeogroup.com

- Compensation cables 300/500(600) V
- CST 74C068
- Zero halogen (SH)
- Cables installed outside of the containment area (K3)
- Overall Screen (EG)
- Unarmoured (NA)

### STANDARDS

Product IEC 60584 - 3; NF C42 - 324

Test IEC 60332 - 3 - 23; IEC 60754 - 1; IEC 61034 - 2; NF C32 - 070/C1

### CHARACTERISTICS

	Copper Braid
Halogen free	IEC 60754 - 1
	1.34 mm <sup>2</sup>
	1.5 mm
Diameter over insulation	2.7 mm
Diameter over screen	16.1 mm
Minimum outer diameter	19.1 mm
Maximum outer diameter	21.7 mm
( )	494 kg/km
Uo/U (Um)	300/500 V
Fire retardant	NF C 32070 C1; IEC 60332 - 3 - 24 (cat.B)
	EN/IEC 61034 - 2
Electro magnetic interference resistance	Yes



Halogen free  
IEC 60754 - 1



Uo/U (Um)  
300/500 V



Fire retardant  
NF C 32070 C1; IEC  
60332 - 3 - 24 (cat.B)



EN/IEC 61034 - 2



Electro magnetic  
interference  
resistance  
Yes



Operating temp.  
- 20 ... 60 ° C



Max. conductor  
temp. in service  
90 ° C

操作度范	- 20 ... 60 ° C
Max. conductor temperature in service	90 ° C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:  
10 x outer diameter  
To be doubled during laying operations



Halogen free  
IEC 60754 - 1



Uo/U (Um)  
300/500 V



Fire retardant  
NF C 32070 C1; IEC  
60332 - 3 - 24 (cat.B)



EN/IEC 61034 - 2



Electro magnetic  
interference  
resistance  
Yes



Operating temp.  
- 20 ... 60 ° C



Max. conductor  
temp.in service  
90 ° C