



Diam.: 11.4 ± 0.5 mm

CONTACT

Market information
industryprojects.business@lynxeogroup.com

Torsion resistant, PUR, screened control cables

STANDARDS

Producto Especificaciones Nexans

Application

Control cable WINDLINK® Control C-PUR was specifically designed for wind turbines. These cable is used where cold flexibility and torsion resistance are required. It is therefore a suitable connection for electrical equipments in harsh environments.

Product characteristics

- Suitable for torsion up to $\pm 100^\circ/\text{m}$
- Vibration resistant
- Flame retardant according to IEC 60332-1-2
- Oil resistant according to EN 60811-2-1
- Halogen free according to IEC 60754
- Ozone resistant according to EN 60811-2-1 clause 8
- UV resistant according to IEC 60068-2-5 (only with black outer sheath)

Design

Conductor

Bare copper stranded according to IEC 60228 cl. 6

Insulation

Polyolefine compound

Core indication according to DIN VDE 0293

JZ/OZ: black numbered with/without green-yellow ground wire from 3 conductors

Assembly

Center: filler

Conductors twisted in layers + talc + non woven tape

(TP) Conductors twisted in pairs + Polyester tape + Al/polyester tape (Alu outside)

Inner sheath

Polyurethane compound + non woven tape

(TP) without inner sheath

Screen

Tinned copper braid, coverage $85 \pm 5\%$ + non woven tape

Sheath

Polyurethane compound, matt surface, colour black Ral 9005 or grey Ral 7001



Tensión nominal de servicio U₀/U
300/500 V



Ambient dynamic operating temperature, range
-30 ... 80 °C



Ambient static op. temp
-40 ... 80 °C



Corrosividad de los gases
-



Resistente al fuego
-



Acorde con normativa RoHS
SI



Resistencia a aceites
-



Resistencia a radiaciones ultravioletas
-

CHARACTERISTICS

Características de construcción

Construction type	5 x 2 x 0.75
Material del conductor	-
Aislamiento	-
Formación	-
Insulation colour	-
Pantalla	-
Cubierta interior	-
Cubierta exterior	-

Características dimensionales

Número de conductores	10
diámetro del conductor (mm)	-
Insulation sheath thickness	- mm
Sección del conductor	0,75 mm ²
Diámetro exterior nominal	11,4 mm
Inner sheath thickness	- mm
Contenido de cobre	109 kg/km
Nominal outer sheath thickness	- mm
Minimum cable diameter	- mm
Maximum cable diameter	- mm
Peso aproximado	184 kg/km

Características eléctricas

Resistance of inner conductor (DC)	- Ohm/km
Tensión nominal de servicio U ₀ /U	300/500 V
Max. Electrical Resistance AC 60Hz 70°C	- Ohm/km
Max. Electrical Resistance AC 60Hz 90°C	- Ohm/km
Test voltage	3000 V
Inductive reactance	- Ohm/km
Operating capacitances	- mF/km
Permissible short circuit current	- kA
Operating voltage - range	- kV
Maximum operating voltage	-
Impedancia de transferencia	-

Características mecánicas

Mechanical stress	15 N/mm ²
Tensile strength	- N
Maximum tensile load	- N
Torsion stress	- °/m

Características de uso

Ambient dynamic operating temperature, range	-30 ... 80 °C
Ambient static operating temperature, range	-40 ... 80 °C
Corrosividad de los gases	-
Minimum bending radius, occasionally moving	15 (xD)

Características de uso

Minimum bending radius, fixed installation	6 (xD)
Resistente al fuego	-
Acorde con normativa RoHs	Si
Resistencia a aceites	-
Resistencia a radiaciones ultravioletas	-
Resistencia al ozono	-
Temperatura máxima del conductor	- °C
Temperatura máxima del conductor en corto-circuito	- °C
Installation temperature, range	- °C
Temperatura ambiente de utilización (rango)	- °C

SELLING AND DELIVERY INFORMATION

Marking e.g.

NEXANS INTERCOND - Week/Year of production - WINDLINK Control C-PUR - 300/500V n x/G yy mm² shielded twist control cable

n: number of conductors

x/G: without/with Yellow/Green conductor

yy: section of conductor

Meter marking