

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

Halogenfree, shielded data transmission cables LiHCH / LiHCH (TP)

STANDARDS

Product

Application

The cable WINDLINK® Data LSOH shielded was specifically designed for wind turbines. These cable is used for data transmission where high flexibility, torsion - and oil - resistance are required. It is therefore a suitable connection for electrical panels and sensors.

Product characteristics

- Suitable for torsion up to $\pm 150^\circ / \text{m}$ (from -20°C up to 50°C)
- Vibration resistant
- Low smoke according to IEC 61034 - 2
- Flame retardant according to IEC 60332 - 1 - 2
- Oil resistant according to EN 60811 - 2 - 1 and special oils used in wind turbines
- Halogen free according to IEC 60754
- UV resistant according to IEC 60068 - 2 - 5
- Ozone resistant according to EN 60811 - 2 - 1 clause 8



IEC 60332 - 1 - 2



Gases corrosivity
IEC 60754 - 1; IEC
60754 - 2; EN
50525 - 1 Anx C



IEC 61034 - 2



Oil resistance
IEC 60811 - 2 - 1



U.V resistance
IEC 60068 - 2 - 5



Max. conductor
temp. in service
- $^\circ \text{C}$



Operating temp.
- $40 \dots 90^\circ \text{C}$



Ambient dynamic
operating
temperature,
range
- $30 \dots 80^\circ \text{C}$

CHARACTERISTICS

	4 G 1.5
	Bare copper class 5
Lay Up	Please request detailed data sheet
Insulation colour	Black w. number + yellow/green
	Tinned copper braid, coverage 65%
Sheath colour	Black - RAL 9005
	3
	1.5 mm ²
Conductor diameter (mm)	-
Insulation sheath thickness	- mm
Diameter over braid	- mm
Nominal outer sheath thickness	- mm
Minimum cable diameter	- mm
Maximum cable diameter	- mm
Nominal outer diameter	8.2 mm
()	122 kg/km
Copper content	- kg/km
20 ° C DC	- Ohm/km
Max. Electrical Resistance AC 60Hz 70 ° C	- Ohm/km
Max. Electrical Resistance AC 60Hz 90 ° C	- Ohm/km
Inductive reactance	- Ohm/km
Operating capacitances	- mF/km
Permissible short circuit current	- kA
Maximum operating voltage	-
Nominal Voltage	250 V
	1500 V
Transfer impedance	25
Permissible current rating in open air	- A
Mechanical stress	15 N/mm ²
Torsion stress	150 ° /m
Maximum tensile strength	- N/mm ²
	IEC 60332 - 1 - 2
Gases corrosivity	IEC 60754 - 1; IEC 60754 - 2; EN 50525 - 1 Anx C
	IEC 61034 - 2
Oil resistance	IEC 60811 - 2 - 1
U.V resistance	IEC 60068 - 2 - 5
Ozone resistance	IEC 60811 - 100 & IEC 60811 - 403
Max. conductor temperature in service	- ° C
Short - circuit max. conductor temperature	- ° C

Ambient installation temperature	- ° C
操作度范	- 40 ... 90 ° C
Ambient dynamic operating temperature, range	- 30 ... 80 ° C
Ambient static operating temperature, range	- 40 ... 80 ° C
Minimum bending radius, occasionally moving	6 (xD)
Minimum bending radius, fixed installation	4 (xD)

SELLING AND DELIVERY INFORMATION

Marking e.g.

NEXANS INTERCOND - Week/Year of production - WINDLINK LiHCH n x yy mm²

n: number of conductors

yy: section of conductor

Meter marking