



Reference: 10091325
 Country Ref.: 01096682
 EAN 13: 3427580103728

CONTACT

Market information
 industryprojects.business@lynx^{eo}
 ogroup.com

Power and control cables armed with lead sheath 0.6/1kV, XP C 32-111, aliphatic and aromatic hydrocarbons resistant, are AD8 and AG4. These cables are fire retardant NF C 32070 C1.

STANDARDS

Product IEC 60228; XP C 32-111

Test IEC 60332-3-24; NF C32-070/C1

Applications

These power and control cables are used for electricity supply in **low voltage installation system**. They are well adapted to **underground use** in industrial applications, in moist areas, where **hydrocarbon and mechanical protections are needed**. **The lead sheath brings an enhanced resistance to aromatics hydrocarbons.**

Design

Conductor:

- Solid plain copper: 1.5 to 4 mm²
- Stranded plain copper or aluminium: 6 to 630 mm²

Insulation:

- Cross-linked polyethylene (XLPE)

Bedding (optional)

Inner sheath:

- Polyvinyl chloride (PVC) Colour: black

Lead cover

Armour:

- Paraffin-waxed crepe paper
- Double steel tape (STA)

Outer sheath:

- Polyvinyl chloride (PVC). Colour: black.

Core identification

- 2 to 5 cores: according to HD 308 S2
- > 5 cores: printed numbers
- > 5G cores: printed numbers + green/yellow core

Marking

U-1000 (A)RGPFV - RH Nber of cores and cross-section NF-USE 279 NFC 32070 C1 + meter marking



Conductor flexibility
Stranded class 2



Rated Voltage U_o/U_m
 (Um)
0,6/1 kV



Mechanical resistance
 to impacts
Good



Fire retardant
**NF C 32-070 C1, IEC
 60332-3-24 (cat.C)**



Chemical resistance
**Aliphatic and
 aromatic
 hydrocarbons
 resistant**



Max. conductor temp. in
 service
90 °C



Operating temp.
-20 ... 60 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Copper
Conductor flexibility	Stranded class 2
With Green/Yellow core	Yes
Lead Sheath	Yes

Dimensional characteristics

Number of cores	3
Conductor cross-section	10 mm ²
Neutral conductor section (when smaller)	- mm ²
Ground conductor cross-section	- mm ²
Diameter over inner sheath	12.8 mm
Diameter over lead sheath	15 mm
Diameter over armour	18.5 mm
Minimum outer diameter	17.6 mm
Maximum outer diameter	23.2 mm
Approximate weight	1345 kg/km

Electrical characteristics

Rated Voltage U ₀ /U (U _m)	0,6/1 kV
---	----------

Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

Usage characteristics

Fire retardant	NF C 32-070 C1, IEC 60332-3-24 (cat.C)
Chemical resistance	Aliphatic and aromatic hydrocarbons resistant
Max. conductor temperature in service	90 °C
Operating temperature, range	-20 ... 60 °C

SELLING AND DELIVERY INFORMATION

Other references available on request.

According to NF C 32111, these cables can be manufactured form U 1000 R2V. In such case the diameters and the weights will be a little bit different from the above ones.

Bending radius: 8x outer diameter
 To be doubled during laying operations



Conductor flexibility
Stranded class 2



Rated Voltage U₀/U (U_m)
 0,6/1 kV



Mechanical resistance to impacts
Good



Fire retardant
NF C 32-070 C1, IEC 60332-3-24 (cat.C)



Chemical resistance
Aliphatic and aromatic hydrocarbons resistant



Max. conductor temp. in service
90 °C



Operating temp.
-20 ... 60 °C