



**Reference:** 10101846  
**EAN 13:** 3427580238741

### CONTACT

Market information  
 industryprojects.business@lynxgroup.com

- Instrumentation cables 300 V
- Individual & Overall Screen (IOS)
- **Low smoke, low halogen (LSLH)**
- **Oil resistant**

### STANDARDS

**Product** IEC 60228

**Test** IEC 60332-3-22 Cat.A; IEC 60754; IEC 61034

### APPLICATIONS

These cables are intended for transmission of analogue and digital signals. They allow transmission over long distances at high pulse rates. The individual screening of each pair limits the consequences of crosstalk. These cables are used in industrial installations such as refineries, chemical plants etc...

### Design

#### Conductor:

Stranded bare copper (class 2)

#### Insulation:

Polyethylene (PE)

#### Individual screen:

Tinned copper drain wire

Aluminium/polyester tape

#### Overall screen:

Tinned copper drain wire

Aluminium/polyester tape

#### Outer sheath:

Polyvinyl chloride (PVC)

Special low smoke, low halogen (LSLH)

Colour: black or blue

Fire retardant: IEC 60332-3-22(A), limiting oxygen index > 30 as par ASTM D 2863

Low smoke: IEC 61034-2, transmittance > 40 %

Low halogen: IEC 60754-1 HCL < 6 %

### Core identification

Pair: Black/white  
 For multipair: White core printed with pair number



Conductor flexibility  
 Stranded class 2



Fire retardant  
 EN IEC 60332-3-22 (cat. A)



Oil resistance  
 IEC 60754-1



Smoke density  
 Low



Operating temp.  
 -20 ... 60 °C



Max. conductor temp. in service  
 70 °C

### Marking

GORSE YYYY RE - 2Y(St)Y - fl PiMF LSLH 300V Nber of pairs & cross-section IEC 60332-3-22(A) + metric marking

### Désignation

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx<sup>eo</sup> is indicative only and shall not be binding. The drawings and designs constituting a representation on the part of Lynx<sup>eo</sup>.

RE: Instrumentation cables  
 2Y: Polyethylene insulation  
 (St): Collective screen

## CHARACTERISTICS

### Construction characteristics

Conductor material	Bare copper
Conductor flexibility	Stranded class 2
Insulation	PE
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Outer sheath	PVC
Sheath colour	Blue

### Dimensional characteristics

Conductor cross-section	0.75 mm <sup>2</sup>
Number of pairs	2
Minimum outer diameter	9.6 mm
Maximum outer diameter	10.6 mm
Approximate weight	135 kg/km

### Electrical characteristics

Operating voltage	300 V
-------------------	-------

### Usage characteristics

Fire retardant	EN IEC 60332-3-22 (cat A)
Oil resistance	ASTM D 1047
Smoke density	Low
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	70 °C
Standard	EN

## ELECTRICAL CHARACTERISTICS

### Electrical data AT 20°C

Cables (mm <sup>2</sup> )	Conductor Resistance max. (Ohm / km)	Insulation Resistance min. (Mohm.km)	Mutual Capacitance at 800 Hz maximum (nF / km)	L/R ratio max (µH / ohm)	Test Voltage (core/core) (V)
0.5	36.7	5 000	115	25	2 000
0.75	24.9	5 000	115	25	2 000
1.34	14.2	5 000	115	40	2 000



Conductor flexibility  
Stranded class 2



Fire retardant  
EN IEC 60332-3-22 (cat A)



Oil resistance  
ASTM D 1047



Smoke density  
Low



Operating temp.  
-20 ... 60 °C



Max. conductor temp. in service  
70 °C

### SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations



Conductor flexibility  
Stranded class 2



Fire retardant  
EN IEC 60332-3-22 (cat A)



Oil resistance  
ASTM D 1047



Smoke density  
Low



Operating temp.  
-20 ... 60 °C



Max. conductor temp. in service  
70 °C