



Reference: 10112052
EAN 13: 3427580200465

CONTACT

Market information
industryprojects.business@lynxgroup.com

- Instrumentation cables 300/500 V
- XLPE insulation (Part 1)
- Unarmoured (Type 1)
- Individual & Overall Screen (IOS)
- Oil resistant

STANDARDS

Test IEC 60332 - 3 - 22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to transmit analogue or digital signals in measurement and process control where chemicals may be present. The individual screening of each pair limits the consequence of crosstalk..

Design

Conductor:

Solid, stranded or flexible bare copper

Insulation:

Cross - linked polyethylene (XLPE)

Individual screen:

Binder tape

Tinned copper drain wire,

Aluminium/polyester tape

Binder tape

Overall screen:

Binder tape

Tinned copper drain wire,

Aluminium/polyester tape

Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request.

Core identification

Pair: black - white

White core printed with pair number

On request: according to PAS 5308 part 1



Uo/U (Um)
300/500 V



Fire retardant
EN IEC 60332 - 3 - 22 (cat
A)



Oil resistance
Yes



Electromagnetic
interference resistance
Yes



Operating temp.
-20 ... 60 ° C



Maximum conductor temp.
service
90 ° C

Marking

NEXANS 279 XLPE/IND. + OA/SCR/PVC 300/500V Nber of pairs & cross - section
Cu IEC 60332 - 3 - 22(A) MM.YYYY Manufacturing number + metric marking

Standards

PAS 5308 Part 1/type 1 (Design guide - lines)

BS EN 60228 - 2005

BS EN 50290 - 2 - 29

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx^{eo} is indicative only and shall not be binding on Lynx^{eo} or be treated as constituting a representation on the part of Lynx^{eo}.

CHARACTERISTICS

	1
	XLPE(가)
Individual screen	Tinned copper drain wire + aluminium/polyester tape
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Protection	no
Number of pairs	5
	0.5 mm ²
	0.8 mm
Diameter over insulation	1.8 mm
Minimum outer diameter	13.0 mm
Maximum outer diameter	14.4 mm
()	210 kg/km
U _o /U (U _m)	300/500 V
Fire retardant	EN IEC 60332 - 3 - 22 (cat A)
Oil resistance	Yes
Electro magnetic interference resistance	Yes
操作度范	- 20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	PAS

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332 - 1 or IEC 60332 - 3 - 24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



U_o/U (U_m)
300/500 V



Fire retardant
EN IEC 60332 - 3 - 22 (cat A)



Oil resistance
Yes



Electro magnetic
interference resistance
Yes



Operating temp.
- 20 ... 60 °C



Max. conductor temp.in
service
90 °C