



Reference: 10134777
EAN 13: 3427580318283

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

- Instrumentation cables 170/300 V
- Overall Screen (OS)
- **Oil resistant**

STANDARDS

Test IEC 60332-3-22 Cat.A

APPLICATIONS

These instrumentation and communication cable are used to **transmit analogue or digital signals in measurement and process control**. They are well adapted to **underground use in industrial application where chemical and mechanical protections are needed (refinery areas, chemical plant...)**.

Design

Conductor:

Stranded bare copper class 2

Insulation:

Cross-linked polyethylene (XLPE)

Overall screen:

Polyester tape

Tinned copper drain wire,

Aluminium backed polyester tape

Inner sheath:

Polyvinyl chloride (PVC).

Colour : black

Armour:

Galvanized steel wires (SWA)

Outer sheath:

Polyvinyl chloride (PVC).

Colour: black.

Other colour on request.

Core identification

Pair: white - black

Quad: white - black - red - blue (2 pair cables assembled as a quad)

White core printed with pair number



Rated Voltage Uo/U (Um)
170/300V



Mechanical resistance to impacts
Good



Fire retardant
EN IEC 60332-3-22 Cat.A



Oil resistance



Electro magnetic interference resistance
Yes



Operating temp.



Max. conductor temp.in service
90 °C

Marking

EN IEC 60332-3-22 Cat.A
 EN IEC 60332-3-22(A) MM YYYY Manufacturing number + metric marking

Standards

All data are design guidelines and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynxéo is indicative only and shall not be binding on Lynxéo or be treated as constituting a representation on the part of Lynxéo.

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Type of conductor	Stranded, class 2
Insulation	XLPE (Cross-linked Polyethylene)
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Inner sheath	PVC
Armour type	Galvanized steel wires
Outer sheath	PVC
Protection	Yes

Dimensional characteristics

Number of pairs	1
Conductor cross-section	0.75 mm ²
Conductor diameter	1.1 mm
Diameter over insulation	1.58 mm
Diameter over inner sheath	5.4 mm
Diameter over armour	7.2 mm
Minimum outer diameter	9.5 mm
Maximum outer diameter	10.5 mm
Approximate weight	194 kg/km

Electrical characteristics

Rated Voltage U ₀ /U (Um)	170/300V
--------------------------------------	----------

Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

Usage characteristics

Fire retardant	EN IEC 60332-3-22 (cat A)
Oil resistance	Yes
Electro magnetic interference resistance	Yes
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Standard	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.

Minimum bending radius:



Rated Voltage U₀/U (Um)
170/300V



Mechanical resistance to impacts
Good



Fire retardant
EN IEC 60332-3-22 (cat A)



Oil resistance
Yes



Electro magnetic interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp. in service
90 °C

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



Rated Voltage U₀/U
(U_m)
170/300V



Mechanical resistance
to impacts
Good



Fire retardant
EN IEC 60332-3-22
(cat A)



Oil resistance
Yes



Electro magnetic
interference resistance
Yes



Operating temp.
-20 ... 60 °C



Max. conductor temp. in
service
90 °C