



Reference: 10135130
EAN 13: 3427580321719

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

- Instrumentation cables 170/300 V
- Individual & Overall Screen (IOS)
- Oil resistant

STANDARDS

Test IEC 60331; IEC 60332-3-22 Cat. A

APPLICATIONS

These Instrumentation and communication are used to transmit analogue or digital signals in measurement and process control. They are well adapted tounderground use in industrial applications where chemical and mechanical protections are needed (refinery areas, chemical plant...). The individual screening of each pair limits the consequence of crosstalk. They maintain circuit integrity when exposed to fire.

Design

Conductor:

Stranded bare copper class 2

Insulation:

Silicone rubber (Sil)

Individual screen:

Polyester tape

Tinned copper drain wire

Aluminium/polyester tape

Polyester tape

Overall screen:

Polyester tape

Tinned copper drain wire

Aluminium/polyester tape

Inner sheath:

Low Smoke Zero Halogen (LSZH)

Armour:

Galvanized steel wires (SWA)

Outer sheath:

Polyvinyl chloride (PVC)

Colour: black

Other colour on request.
耐火 60331 其他颜色 可燃 EN IEC 60332-3-22 耐油 是 (cat A)

Core identification

Pair: white - black

White core printed with pair number

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx^{eo} is indicative only and shall not be binding on Lynx^{eo} or be treated as constituting a representation on the part of Lynx^{eo}.

NEXANS 279 SIL IND. 4A. SCR/LSZH/SWA/PVC 170/300V Nber of pairs & cross-section
Cu IEC 60331 IEC 60332-3-22 (A) MM YYY Y Manufacturing number + metric marking



额定电压U₀/U
170/300V



机械耐冲击性能
好



耐火
IEC 60331



可燃
EN IEC 60332-3-22
(cat A)



耐油
是



抗电磁干扰
是



操作温度
-20 ... 60 ° C



芯线最高静止温度
90 ° C

CHARACTERISTICS

结构特性

导体材料	裸铜线
导体类型	Stranded, class 2
绝缘	硅树脂橡胶
线对屏蔽	Tinned copper drain wire + aluminium/polyester tape
总屏蔽	Tinned copper drain wire + aluminium/polyester tape
内护套	Low smoke, zero halogen thermoplastic compound
铠装类型	镀锌钢丝
外护套	聚氯乙烯
防护	Yes

尺寸特性

线对数	20
导线截面	1 mm ²
导线直径	1.28 mm
绝缘外径	2.44 mm
Diameter over inner sheath	26.5 mm
铠装外径	29.0 mm
外径最小值	29.3 mm
Maximum outer diameter	34.2 mm
近似重量	1768 kg/km

电气特性

额定电压U ₀ /U	170/300V
-----------------------	----------

机械特性

机械耐冲击性能	好
---------	---

使用特性

耐火	IEC 60331
阻燃	EN IEC 60332-3-22 (cat A)
耐油	是
抗电磁干扰	是
操作温度范围	-20 ... 60 ° C
芯线最高静止温度	90 ° C
标准	EN

SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332-1 or IEC 60332-3-24(C) and enhanced hydrocarbon resistance on request.



额定电压U₀/U
170/300V



机械耐冲击性能
好



耐火
IEC 60331



阻燃
EN IEC 60332-3-22
(cat A)



耐油
是



抗电磁干扰
是



操作温度
-20 ... 60 ° C



芯线最高静止温度
90 ° C

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations

Tinned copper conductors available on request



额定电压 U_0/U
170/300V



机械耐冲击性能
好



耐火
IEC 60331



阻燃
EN IEC 60332-3-22
(cat A)



耐油
是



抗电磁干扰
是



操作温度
-20 ... 60 °C



芯线最高静止温度
90 °C