



Reference: 10171708
EAN 13: 3427650095823

CONTACT

Market information
industryprojects.business@lyn
xeogroup.com

International Designation: MPRX 331 0.6/1KV 3X1.5

FIRE RESISTANT POWER CABLES

STANDARDS

Installation IEC 60092-350

Test a; IEC 60331; IEC 60332-3 Cat. A; IEC 60754-1; IEC 61034

International IEC 60298

APPLICATION

MPRX®331 0.6/1 kV fire resistant power and control cables maintain circuit integrity in case of fire by meeting performances requirements from the IEC 60331 series for 180 minutes. They are used for detection and warning systems not subject to mechanical risks.

The highly flexible MPRX®331 FLEXISHIP® range is recommended for installations and connections in narrow spaces where an optimal bending radius is required. Designed with halogen-free fire retardant materials, they provide optimum safety for people and maximal asset protection against all risks of fire.

Design

1. Conductor
Stranded bare copper, class 2 or class 5 for FLEXISHIP®
2. Insulation
Mica tape + XLPE (cross-linked polyethylene)
3. Outer sheath
(Filler if necessary)
Polyolefin SHF1
Colour: orange

Example of marking:

LYNXEO 279 MPRX 331 or MPRX 331 FLEXISHIP 0.6/1 kV "n" x (orG) "s" 90° C IEC 60092-353 IEC 60332-3-22 Cat. A IEC 60331-1/21 "ww/yy" * CE* + metric marking

Core Identification

- 1 x: black
- 2 x: brown-blue
- 3 x: brown-black-grey
- 3G: brown-blue-green/yellow
- 4 x: brown-black-grey-blue
- 4G: brown-black-grey-green/yellow
- > 5 cores: n x: white with printed numbers / nG: white with printed numbers + green/yellow core



无卤
IEC 60754-1



导线柔软度
绞和等级2



额定电压U_o/U
0.6/ 1 (1.2) kV



耐火
IEC 60331-1 or -2



阻燃
EN IEC 60332-3-22
(cat A)



烟密度
IEC 61034



气体腐蚀性
低 IEC 60754-2



操作温度
-30 ... 80 ° C

CHARACTERISTICS

结构特性

导体材料	裸铜线
无卤	IEC 60754-1
护套颜色	橙
绝缘	交联聚乙烯+云母带
填充物/内护套材料	如需填充物
外护套	聚烯烃
导线柔软度	绞和等级2
有绿/黄芯线	无

尺寸特性

芯线数	3
导线截面	1.5 mm ²
外径最小值	10.6 mm
Maximum outer diameter	12.2 mm
近似重量	127 kg/km
标称外径	11.3 mm

电气特性

额定电压U ₀ /U	0.6/ 1 (1.2) kV
允许通过的短路电流	0.2 kA
露天允许通过的额定电流	16 A
20° C时导体的最大直流电阻	12.1 Ohm/km

使用特性

耐火	IEC 60331-1 or -2
阻燃	EN IEC 60332-3-22 (cat A)
烟密度	IEC 61034
气体腐蚀性	低 IEC 60754-2
操作温度范围	-30 ... 80 ° C
芯线最高静止温度	90 ° C

OTHER CHARACTERISTICS

Test Voltage

AC between

cores.....
 .. 3.5 kV AC

Minimum bending radius for fixed installations

- MPRX®

331..... 6 x
 outer diameter

- MPRX® 331 FLEXISHIP®..... 5 x
 outer diameter