



**Reference:** 10176341  
**Country Ref.:** 01272427  
**EAN 13:** 3427580465062

### CONTACT

Market information  
 industryprojects.business@lynx<sup>eo</sup>.group.com

Control cables CST 74C068 for nuclear power plants, 500V halogen-free. These cables, installed outside the containment area (K3), are unarmed and designed with copper braid shield.

### STANDARDS

**Produkt** IEC 60228

**Tests** IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

### APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

### CONSTRUCTION

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross linked

Assembling:

- Polyester tape (optional)

Overall screen:

- Copper wire braid (CWB) R ≥ 80%

Outer sheath:

- Low smoke, zero halogen (LSZH)

- Colour: Grey

#### Core identification

Black cores printed with white numbers

Optional: with Y/G core

#### Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogenfrei  
 IEC 60754-1; IEC 60754-2



Betriebstemp.  
 -20 ... 60 °C



Rauchdichte  
 EN/IEC 61034-2



Flammwidrig  
 NF C 32070 C1;  
 IEC 60332-3-24  
 (cat.B)



Elektromagnetisch  
 geschirmt  
 Ja



UV Beständigkeit  
 Ja



Life cycle 60years  
 Ja



Max. Betriebstemp.  
 am Leiter  
 90 °C

**CHARACTERISTICS****Konstruktionsmerkmale**

Leitermaterial	blank
Leitertype	Stranded, class 2
Isolierung	Halogen-free
Schirm	Copper Braid
Außenmantel	LSZH, raucharm & halogenfrei
Halogenfrei	IEC 60754-1; IEC 60754-2

**Abmessungsmerkmale**

Leiterquerschnitt	1,5 mm <sup>2</sup>
Aderanzahl	12
Leiterdurchmesser	1,5 mm
Durchmesser über Isolierung	2,84 mm
Diameter over screen	12,3 mm
Außendurchmesser Mindestwert	15,2 mm
Maximaler Außendurchmesser	17,3 mm
Nettogewicht ca.	489 kg/km

**Elektrische Eigenschaften**

Max. Gleichstromwiderstand des Leiters bei 20° C	12,1 Ohm/km
Maximum DC resistance of the conductor at 90°C	15,400 Ohm/km
Reactance at 50 Hz	0,094 Ohm/km
Short Circuit Current 0,3 s Max	0,39 kA
Short Circuit Current 1 s Max	0,21 kA
Impedance at 50 Hz	12,1 Ohm
Spannungsabfall	24,8 V/A.km
Calorific Power	3,9 MJ/m

**Anwendungsmerkmale**

Betriebstemperatur	-20 ... 60 °C
Rauchdichte	EN/IEC 61034-2
Flammwidrig	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Elektromagnetisch geschirmt	Ja
UV Beständigkeit	Ja
Life cycle 60years	Ja
Max. Betriebstemperatur am Leiter	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

**SELLING AND DELIVERY INFORMATION****Minimum bending radius:**

10 x outer diameter  
To be doubled during laying operations