



Reference: 10186721  
EAN 13: 3427580519581

#### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>.com

- Instrumentation cables 170/300 V
- With lead cover (LC)
- Overall Screen (OS)
- Aliphatic and aromatic hydrocarbons resistant

#### STANDARDS

Test IEC 60332 - 3 - 22 Cat.A

#### APPLICATIONS

These instrumentation and communication cables are used to transmit analogue or digital signals in measurement and process control. They are well adapted to underground use in industrial applications, in moist areas, where hydrocarbon and mechanical protection are needed. The lead cover brings an enhanced resistance to aromatics hydrocarbons.

#### Design

##### Conductor:

Stranded bare copper class 2

##### Insulation:

Cross - linked polyethylene (XLPE)

##### Overall screen:

Polyester tape

Tinned copper drain wire,

Aluminium backed polyester tape

##### Inner sheath:

Polyvinyl chloride (PVC)

Colour: black

##### Lead sheath:

##### Bedding (intermediate sheath):

Polyvinyl chloride (PVC)

Colour: black

##### Armour:

Galvanized steel wires (SWA)

##### Outer sheath:

Polyvinyl chloride (PVC)

Colour: black



Uo/U  
(Um)  
170/300V



Mechanical  
resistance to  
impacts  
Good



Fire  
retardant  
EN IEC  
60332-3  
Cat. A)



Other colour on request.  
Core identification  
Pair: white/black  
Quad: white/black - red/blue  
White core marked with pair number  
resistant



Electro magnetic  
interference  
resistant  
Yes



Operating temp.  
-20 ... 60 ° C



Max. conductor  
temp. in service



Min. dynamic  
operating bending  
295.0 mm

#### Marking

NEXANS 279 XLPE/CA-SCR/PVC/LC/PVC/SWA/PVC 170/300V, Number of pairs & dimensions in IEC 60332-3 or 22(A) Min. dynamic operating bending radius  
All drawings, designs, specifications, plans and particulars of weights, size and dimensions shall not be binding on Lynx<sup>eo</sup> or be treated as constituting a representation on the part of Lynx<sup>eo</sup>.

#### Standards

## CHARACTERISTICS

	2 ( )
	XLPE(가 )
Overall screen	Tinned copper drain wire + aluminium/polyester tape
Lead Sheath	Yes
Intermediate sheath	PVC
Armour type	
Protection	Yes
Number of pairs	10
	1.5 mm <sup>2</sup>
	1.5 mm
Diameter over insulation	2.16 mm
Diameter over inner sheath	17.3 mm
Diameter over lead sheath	19.7 mm
Diameter over intermediate sheath	21.7 mm
Diameter over armour	24.2 mm
Minimum outer diameter	26.8 mm
Maximum outer diameter	29.5 mm
( )	2013 kg/km
U <sub>o</sub> /U (U <sub>m</sub> )	170/300V
Mechanical resistance to impacts	Good
Fire retardant	EN IEC 60332 - 3 - 22 (cat A)
Chemical resistance	Aliphatic and aromatic hydrocarbons resistant
Electro magnetic interference resistance	Yes
操作度范	- 20 ... 60 ° C
Max. conductor temperature in service	90 ° C
Minimum dynamic operating bending radius	295.0 mm
Standard	EN

## SELLING AND DELIVERY INFORMATION

Other fire performances IEC 60332 - 1 or IEC 60332 - 3 - 24(C) on request.



U<sub>o</sub>/U  
(U<sub>m</sub>)  
170/300V



Mechanical  
resistance to  
impacts  
Good



Fire retardant  
EN IEC  
60332 - 3 - 22 (cat  
A)



Chemical  
resistance  
Aliphatic and  
aromatic  
hydrocarbons  
resistant



Electro magnetic  
interference  
resistance  
Yes



Operating temp.  
- 20 ... 60 ° C



Max. conductor  
temp. in service  
90 ° C



Min. dynamic  
operating bending  
rad.  
295.0 mm

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations

Tinned copper conductors available on request



U<sub>0</sub>/U  
(U<sub>m</sub>)  
170/300V



Mechanical  
resistance to  
impacts  
Good



Fire retardant  
EN IEC  
60332 - 3 - 22 (cat  
A)



Chemical  
resistance  
Aliphatic and  
aromatic  
hydrocarbons  
resistant



Electro magnetic  
interference  
resistance  
Yes



Operating temp.  
- 20 ... 60 ° C



Max. conductor  
temp. in service  
90 ° C



Min. dynamic  
operating bending  
rad.  
295.0 mm