



Reference: 10189886
Country Ref.: 01272413
EAN 13: 3427580539527

CONTACT

Market information
 industryprojects.business@lynxéogroup.com

Low voltage cables CST 74C068 for nuclear power plants, 0.6/1kV halogen-free. These cables are intended to be installed outside the containment area (K1).

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These low voltage cables are used for lighting system power supply, engine power supply and solenoid valve power supply.

DESIGN

Conductor: Stranded bare copper or aluminium (class 2)

Insulation: Cross-linked halogen free (SH)

Covering (optional): Halogen free

Outer sheath: Low smoke, zero halogen (LSZH)
 Colour: Blue

Core identification

According to HD308 S2

Marking

LYNXEO 279 Nber of cores & cross-section Cu/Al CST 74 C 068 00 K3 SH 0.6/1 (1.2) kV YYYY Manufacturing number + metric marking

STANDARD

IEC 60332-3-23(B)

Quality insurance according to RCC-E



Halogen free
 IEC 60754-1



Rated Voltage Uo/U (Um)
 0.6/ 1 (1.2) kV



Fire retardant
 NF C 32070 C1; IEC 60332-3-24 (cat.B)



Smoke density
 EN/IEC 61034-2



Operating temp.
 -20 ... 60 °C



Max.conductor temp.in service
 90 °C

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Outer sheath	Halogen-free
Halogen free	IEC 60754-1
With Green/Yellow core	Yes

Dimensional characteristics

Conductor cross-section	1.5 mm ²
Number of cores	3
Conductor diameter	1.55 mm
Diameter over insulation	2.95 mm
Minimum outer diameter	10.3 mm
Maximum outer diameter	11.5 mm
Approximate weight	198 kg/km

Electrical characteristics

Rated Voltage U _o /U (U _m)	0.6/ 1 (1.2) kV
---	-----------------

Usage characteristics

Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Smoke density	EN/IEC 61034-2
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

8 x outer diameter
To be doubled during laying operations



Halogen free
IEC 60754-1



Rated Voltage U_o/U (U_m)
0.6/ 1 (1.2) kV



Fire retardant
NF C 32070 C1; IEC 60332-3-24
(cat.B)



Smoke density
EN/IEC 61034-2



Operating temp.
-20 ... 60 °C



Max. conductor temp.in
service
90 °C