



Reference: 10194003
EAN 13: 3427580560156

CONTACT

Markets and Products Information
rollingstock.business@lynxgroup.com

- CST 74C068
- Quality insurance according to RCC-E
- Zero halogen (SH)
- Control cables 0.15/0.25 (0.3)kV
- Cables installed outside of the containment area (K3)
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

DESIGN

Conductor: - Stranded plain copper (class 2)

Insulation: - Zero halogen (SH), cross-linked

Assembling: Polyester tape (optional)

Overall screen: - Copper wire braid (CWB) R ≥ 80%

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Core identification

Black cores printed with white numbers

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH
0.15/0.25 (0.3) kV YYYY Manufacturing number + metric marking



无卤
IEC 60754-1; IEC 60754-2



操作温度
-20 ... 60 ° C



烟密度
IEC 61034-2



阻燃
NF C 32070 C1;
IEC 60332-3-24
(cat. B)



抗电磁干扰
是



抗UV
是



Life cycle
60years
是



芯线最高静止温度
90 ° C

CHARACTERISTICS

结构特性

导体材料	裸铜
导体类型	Stranded, class 2
绝缘	无卤
屏蔽	Copper Braid
外护套	低烟无卤
无卤	IEC 60754-1; IEC 60754-2

尺寸特性

导线截面	0.44 mm ²
芯线数	9
导线直径	0.9 mm
绝缘外径	1.8 mm
Diameter over screen	8.5 mm
外径最小值	10.3 mm
Maximum outer diameter	12.3 mm
近似重量	220 kg/km

电气特性

20° C时导体的最大直流电阻	36 Ohm/km
90° C时导体的最大直流电阻	45.900 Ohm/km
Reactance at 50 Hz	0.103 Ohm/km
Short Circuit Current 0,3 s Max	0.13 kA
Short Circuit Current 1 s Max	0.07 kA
Impedance at 50 Hz	36 Ohm
Voltage Drop	73.6 V/A.km
Calorific Power	2 MJ/m

使用特性

操作温度范围	-20 ... 60 ° C
烟密度	IEC 61034-2
阻燃	NF C 32070 C1; IEC 60332-3-24 (cat. B)
抗电磁干扰	是
抗UV	是
Life cycle 60years	是
芯线最高静止温度	90 ° C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations