



Reference: 10194039
EAN 13: 3427580560217

CONTACT

Markets and Products Information
 rollingstock.business@lynx^{eo}group.com

- CST 74C068
- Quality insurance according to RCC-E
- Zero halogen (SH)
- Control cables 0.15/0.25 (0.3)kV
- **Cables installed outside of the containment area (K3)**
- Overall Screen (EG)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

DESIGN

Conductor: - Stranded plain copper (class 2)

Insulation: - Zero halogen (SH), cross-linked

Assembling: Polyester tape (optional)

Overall screen: - Copper wire braid (CWB) R ≥ 80%

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Core identification

Black cores printed with white numbers

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH 0.15/0.25 (0.3) kV YYY YYY Manufacturing number + metric marking



Halogen free
 IEC 60754-1; IEC 60754-2



Operating temp.
 -20 ... 60 °C



Smoke density
 IEC 61034-2



Fire retardant
 NF C 32070 C1;
 IEC 60332-3-24
 (cat.B)



Electro magnetic
 interference
 resistance
 Yes



U.V resistance
 Yes



Life cycle 60years
 Yes



Max. conductor
 temp.in service
 90 °C

CHARACTERISTICS**Construction characteristics**

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Screen	Copper Braid
Outer sheath	LSZH
Halogen free	IEC 60754-1; IEC 60754-2

Dimensional characteristics

Conductor cross-section	0.44 mm ²
Number of cores	27
Conductor diameter	0.9 mm
Diameter over insulation	1.8 mm
Diameter over screen	12.5 mm
Minimum outer diameter	16.5 mm
Maximum outer diameter	19.0 mm
Approximate weight	520 kg/km

Electrical characteristics

Max. DC resistance of the conductor at 20°C	36 Ohm/km
Maximum DC resistance of the conductor at 90°C	45.900 Ohm/km
Reactance at 50 Hz	0.103 Ohm/km
Short Circuit Current 0,3 s Max	0.13 kA
Short Circuit Current 1 s Max	0.07 kA
Impedance at 50 Hz	36 Ohm
Voltage Drop	73.6 V/A.km
Calorific Power	5.1 MJ/m

Usage characteristics

Operating temperature, range	-20 ... 60 °C
Smoke density	IEC 61034-2
Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Electro magnetic interference resistance	Yes
U.V resistance	Yes
Life cycle 60years	Yes
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION**Minimum bending radius:**

10 x outer diameter
To be doubled during laying operations