



Reference: 10195309
 EAN 13: 3427650109605

CONTACT

Market information
 industryprojects.business@lyn
 xeogroup.com

POWER & CONTROL cables with screen

STANDARDS

Product IEC 60228

Installation IEC 60092 - 350; IEC 60092 - 353; IEC 60092 - 360

Test a; IEC 60332 - 1; IEC 60332 - 3 - 22; IEC 60754 - 1; IEC 61034

APPLICATIONS

MPRXCX® 0.6/1 kV armoured power and control cables are used for wiring fixed installations where enhanced mechanical protection and electrical screening is required.

The highly flexible MPRXCX® FLEXISHIP® range is recommended for installations and connections in narrow spaces where an optimal bending radius is required. The sectoral conductors of multicore cables provide further space and weight savings on the cable trays. Designed with halogen-free fire retardant materials, they provide optimum safety for people and maximal asset protection against all risks of fire.

Design

1. Conductor:
Stranded bare copper, class 2
or flexible bare copper, class 5 for FLEXISHIP® types (cross sections 4 mm²)
2. Insulation:
XLPE (cross-linked polyethylene)
3. Inner covering:
(Filler, if necessary)
Lapped
4. Armouring:
Bare copper braid
5. Outer sheath:
Polyolefin SHF1
Colour: black

Example of marking:

LYNXEO 279 MPRXCX or MPRXCX FLEXISHIP Nbr of cores & cross-section
 0.6/1kV 90C IEC 60092 - 353 IEC 60332 - 3 - 22 Cat. A WW YYYY *CE*
 Manufacturing n° + metric marking

Core Identification

- 1 x: black
- 2 x: brown - blue
- 3 x: brown - black - grey
- 3G: brown - blue - green/yellow
- 4 x: brown - black - grey - blue
- 4G: brown - black - grey - green/yellow
- 5 x: white with printed numbers
- 5G: brown - black - grey - blue - green/yellow
- > 5 cores: n x: white with printed numbers
- > 5 cores: nG: white with printed numbers + green/yellow core



Conductor flexibility

2



Halogen free
 IEC 60754 - 1



Uo/U
 (Um)
 0.6/ 1 (1.2) kV



Fire retardant
 EN IEC
 60332 - 3 - 22 (cat
 A)



IEC 60332 - 1



IEC 61034



Gases corrosion
 IEC 60754 - 2



Electro magnetic
 interference
 resistance
 Yes

CHARACTERISTICS

Conductor flexibility	XLPE(가)	2
Armour type		
Conductor shape		
Halogen free		IEC 60754 - 1
Sheath colour		
With Green/Yellow core		
		5
		2.5 mm ²
Nominal outer diameter		12.38 mm
Minimum outer diameter		11.7 mm
Maximum outer diameter		13.4 mm
()		245 kg/km
Permissible current rating in open air		21 A
U _o /U (U _m)		0.6/ 1 (1.2) kV
20 ° C DC		7.41 Ohm/km
Permissible short circuit current		- kA
Fire retardant	EN IEC 60332 - 3 - 22 (cat A)	
		IEC 60332 - 1
		IEC 61034
Gases corrosivity		IEC 60754 - 2
Electro magnetic interference resistance		Yes
操作度范		- 30 ... 80 ° C
Max. conductor temperature in service		90 ° C



Conductor flexibility

2



Halogen free
IEC 60754 - 1



U_o/U
(U_m)
0.6/ 1 (1.2) kV



Fire retardant
EN IEC
60332 - 3 - 22 (cat
A)



IEC 60332 - 1



IEC 61034



Gases corrosivity
IEC 60754 - 2



Electro magnetic
interference
resistance
Yes

OTHER CHARACTERISTICS

Test Voltage
 AC between cores..... 3.5 kV AC

Minimum bending radius for fixed installations

- cable diameter MPRXCX®..... 6 x outer diameter
- cable diameter MPRXCX® FLEXISHIP®..... 5 x outer diameter



Conductor flexibility

2



Halogen free
 IEC 60754 - 1



Uo/U
 0.6/ 1 (1.2) kV



Fire retardant
 EN IEC
 60332 - 3 - 22 (cat
 A)



IEC 60332 - 1



IEC 61034



Gases corrosivity
 IEC 60754 - 2



Electro magnetic
 interference
 resistance
 Yes