



**Reference:** 10215351  
**EAN 13:** 3427580634208

#### CONTACT

Market information  
 industryprojects.business@lynx<sup>eo</sup>.group.com

- Medium voltage cables 6/6 (7.2) kV
- CST 74C068
- Zero halogen (SH)
- **Cables installed outside of the containment area (K3)**
- Unarmoured (NA)

#### STANDARDS

**Product** IEC 60228; IEC 60502-2

**Test** IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

#### APPLICATIONS

These medium voltage cables are used for medium voltage power supply,

#### DESIGN

##### Design

###### Conductor:

Stranded bare copper or aluminium (class 2)

###### Screen:

Semi-conductor

###### Insulation:

Ethylene Propylene Rubber (EPR)

###### Assembling sheath:

Halogen free

###### Inner sheath:

Halogen free

###### Screen:

Semi-conductor

Copper tape

###### Outer sheath:

Low smoke, zero halogen (LSZH)

Colour: Black

#### Core identification

3x: natural cores printed with black numbers

##### Marking

LYN<sup>eo</sup> 279 185 3x185 Alu2 K3 SH 6/6(7.2) kV YYY YYY Manufacturing number + metric marking



Halogen free  
IEC 60754-1



Rated Voltage U<sub>o</sub>/U (Um)  
6/6(7.2) kV



Fire retardant



Smoke density  
EN/IEC 61034-2



Operating temp.  
-20 ~ 60 °C



Max. conductor temp.in service

#### STANDARD

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Lynx<sup>eo</sup> is indicative only and shall not be binding on Lynx<sup>eo</sup> or be treated as constituting a representation on the part of Lynx<sup>eo</sup>.

**CHARACTERISTICS****Construction characteristics**

Conductor material	Aluminum
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Outer sheath	Halogen-free
Halogen free	IEC 60754-1

**Dimensional characteristics**

Conductor cross-section	185 mm <sup>2</sup>
Number of cores	3
Minimum outer diameter	62.9 mm
Maximum outer diameter	69.3 mm
Approximate weight	625 kg/km
Diameter over screen	58.0 mm

**Electrical characteristics**

Rated Voltage U <sub>0</sub> /U (Um)	6/6(7.2) kV
--------------------------------------	-------------

**Usage characteristics**

Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Smoke density	EN/IEC 61034-2
Operating temperature, range	-20 ... 60 °C
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

**SELLING AND DELIVERY INFORMATION**

Minimum bending radius:

8 x outer diameter  
To be doubled during laying operations



Halogen free  
IEC 60754-1



Rated Voltage U<sub>0</sub>/U (Um)  
6/6(7.2) kV



Fire retardant  
NF C 32070 C1; IEC 60332-3-24  
(cat.B)



Smoke density  
EN/IEC 61034-2



Operating temp.  
-20 ... 60 °C



Max. conductor temp.in  
service  
90 °C