



Reference: 10218856
Country Ref.: 2PK698

CONTACT

Markets and Products Information
 rollingstock.business@lynxeogroup.com

COMMUNICATION CABLES

FLAMEX® ETHERNET are intended for the train backbone and the connection to the different devices. They are designed to operate in harsh environmental conditions. FLAMEX® ETHERNET are designed to improve the protection against electromagnetic noises and provides the highest level of reliability and robustness required by the railway industry.

STANDARDS

Product EN 45545-2 (HL3); EN 50264-1

DESIGN

1. Conductor

Stranded tinned copper

2. Insulation

Polyethylene (PE)
 Quad or Pairs assemblies

3. Screen

Tinned copper braid
 Separator tape

4. Outer sheath

Cross-linked material EM 104 or EM 101 acc. EN 50264-1
 Oil, diesel, ozone and UV resistant
 Colour: black or blue

Example of marking: FLAMEX 239 - [4(2xAWG26/19 10Gigabit CAT7)]M S - EDE
 XXXX - week/year / batch number

ADDITIONAL INFORMATION

- Bending radius:
 - Static use: 5 x outer cable diameter
 - For installation and occasional movements: 10 x outer cable diameter



Conductor flexibility
Flexible stranded



Halogen free
 EN 60754-1 & EN 60684-2



Flame retardant
 EN 60332-1-2



Fire retardant
 EN IEC 60332-3-25 (cat D)



Smoke density
 EN/IEC 61034-2



Gases toxicity
 EN 50305-9.2



Minimum operating temperature
 -40 °C



Electro magnetic interference resistance
Yes

CHARACTERISTICS

Construction characteristics

| | |
|-----------------------|-------------------------|
| Conductor material | Tin plated copper |
| Type of cable | CAT 5E |
| Construction type | 4 x 0.50 ² |
| Conductor flexibility | Flexible stranded |
| Outer sheath | Cross-linked compound |
| Sheath colour | Blue |
| Core identification | C |
| Screen | Tinned copper braid |
| Halogen free | EN 60754-1 & EN 60684-2 |

Dimensional characteristics

| | |
|------------------------|----------|
| Nominal outer diameter | 8.5 mm |
| Approximate weight | 96 kg/km |

Usage characteristics

| | |
|--|---------------------------|
| Flame retardant | EN 60332-1-2 |
| Fire retardant | EN IEC 60332-3-25 (cat D) |
| Smoke density | EN/IEC 61034-2 |
| Gases toxicity | EN 50305-9.2 |
| Minimum operating temperature | -40 °C |
| Electro magnetic interference resistance | Yes |
| Chemical resistance | Good |

SELLING AND DELIVERY INFORMATION

A: Color coding for pairs

N°1: white + blue
N°2: white + orange
N°3: white + green
N°4: white + brown

B: Color coding for pairs: N°1: white + blue N°2: yellow + orange

C: Color coding for quads: N°1: white + blue N°2: yellow + orange

D: Color coding for quads: N°1: white + yellow N°2: red + black