



Reference: 10222188  
EAN 13: 3427580646546

### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>.group.com

Control cables CST 74C068 for nuclear power plants, 500V halogen-free. These cables, installed outside the containment area (K3), are unarmed and designed with copper braid shield.

### STANDARDS

Product IEC 60228

Test IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

### APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

### CONSTRUCTION

#### Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

#### Insulation:

- Zero halogen (SH), cross linked

#### Assembling:

- Polyester tape (optional)

#### Overall screen:

- Copper wire braid (CWB)  $R \geq 80\%$

#### Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Core identification

Black cores printed with white numbers

Optional: with Y/G core

Marking

LYNXEO 279 Nber of cores & cross-section Cu EG CST 74 C 068 K3 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



无卤  
IEC 60754-1; IEC 60754-2



操作温度  
-20 ... 60 ° C



烟密度  
EN/IEC 61034-2



阻燃  
NF C 32070 C1;  
IEC 60332-3-24  
(cat. B)



抗电磁干扰  
是



抗UV  
是



Life cycle  
60years  
是



芯线最高静止温度  
90 ° C

## CHARACTERISTICS

## 结构特性

导体材料	裸铜
导体类型	Stranded, class 2
绝缘	无卤
屏蔽	Copper Braid
外护套	低烟无卤
无卤	IEC 60754-1; IEC 60754-2

## 尺寸特性

导线截面	6 mm <sup>2</sup>
芯线数	2
导线直径	2.95 mm
绝缘外径	4.4 mm
Diameter over screen	9.9 mm
外径最小值	12.3 mm
Maximum outer diameter	14.1 mm
近似重量	315 kg/km

## 电气特性

20° C时导体的最大直流电阻	3.08 Ohm/km
90° C时导体的最大直流电阻	3.920 Ohm/km
Reactance at 50 Hz	0.083 Ohm/km
Short Circuit Current 0,3 s Max	1.6 kA
Short Circuit Current 1 s Max	0.86 kA
Impedance at 50 Hz	3.08 Ohm
Voltage Drop	6.4 V/A. km
Calorific Power	2 MJ/m

## 使用特性

操作温度范围	-20 ... 60 ° C
烟密度	EN/IEC 61034-2
阻燃	NF C 32070 C1; IEC 60332-3-24 (cat. B)
抗电磁干扰	是
抗UV	是
Life cycle 60years	是
芯线最高静止温度	90 ° C
Nuclear Classification	Class 1 E Non LOCA/K3

## SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter  
To be doubled during laying operations