



Reference: 10226965
EAN 13: 3427580659904

CONTACT

Markets and Products Information
 rollingstock.business@lynxgroup.com

- CST 74C068
- Quality insurance according to RCC-E
- Zero halogen (SH)
- Control cables 0.3/0.5(0.6)kV
- **Cables installed outside of the containment area (K3)**
- Without Screen (SE)
- Armoured by braid (TZ) or tapes (AR)

STANDARDS

Product IEC 60228

Test a; IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room. Many of them require anti-inductive screen (EMI).

DESIGN

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross-linked

Assembling:

- Polyester tape (optional)

Inner sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Armour:

- Galvanized steel braid (Tz) ≤ 4 conductors
- Steel tapes (Ar) > 4 conductors

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Core identification

Black cores printed with white numbers

Optional: with G/Y core

Marking

LYNXEO 279 Nber of cores & cross-section Cu ARME CST 74 C 068 K3 SH 0.3/0.5 (0.6) kV YYYY Manufacturing number + metric marking



Halogen free
 IEC 60754-1; IEC 60754-2



Rated Voltage U_o/U_m
 (Um)
 0.3/0.5(0.6)kV



Mechanical
 resistance to
 impacts
 Good



Operating temp.
 -20 ... 60 °C



Smoke density
 IEC 61034-2



Fire retardant
 NF C 32070 C1;
 IEC 60332-3-24
 (cat.B)



U.V resistance
 Yes



Life cycle 60years
 Yes

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Halogen-free
Inner sheath	LSZH
Armour type	Double steel tapes
Outer sheath	LSZH
Halogen free	IEC 60754-1; IEC 60754-2

Dimensional characteristics

Conductor cross-section	2.5 mm ²
Number of cores	2
Conductor diameter	1.9 mm
Diameter over insulation	3.1 mm
Diameter over inner sheath	8.3 mm
Diameter over armour	9.3 mm
Minimum outer diameter	11.9 mm
Maximum outer diameter	13.6 mm
Approximate weight	290 kg/km

Electrical characteristics

Max. DC resistance of the conductor at 20°C	7.41 Ohm/km
Maximum DC resistance of the conductor at 90°C	9.440 Ohm/km
Reactance at 50 Hz	0.09 Ohm/km
Short Circuit Current 0,3 s Max	0.65 kA
Short Circuit Current 1 s Max	0.36 kA
Impedance at 50 Hz	7.41 Ohm
Voltage Drop	13.2 V/A.km
Calorific Power	2.4 MJ/m
Rated Voltage U _o /U (U _m)	0.3/0.5(0.6)kV

Mechanical characteristics

Mechanical resistance to impacts	Good
----------------------------------	------

Usage characteristics

Operating temperature, range	-20 ... 60 °C
Smoke density	IEC 61034-2
Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
U.V resistance	Yes
Life cycle 60years	Yes
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E Non LOCA/K3

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations