



Reference: 10263102
EAN 13: 3427580739286

CONTACT

Markets and Products Information
rollingstock.business@lynxéogroup.com

HIGH TEMPERATURE EXTRA-FLEXIBLE POWER CABLES

FLAMEX® EN 50382-2 FX power cables are designed with extra flexible conductors for easier installation. Able to withstand higher operating temperatures, these silicone-based cables allow to save cable weight.

STANDARDS

Product EN 45545-2 (HL3); EN 50382-2; IEC 60228

DESIGN

1. Conductor

Extra flexible class 6 copper according to IEC 60228

- tinned copper for 120° C Class
- plain copper for 150° C Class

Separator: Unweaved tape

2. Insulation

Cross-linked silicone type EI 111 according to EN 50382-1

Colour: black outer layer

Example of marking: FLAMEX SI - EN 50382-2 - Voltage rate (1800V or 3600V) - cross-section mm² - FX - temperature class (150° C) - LYNXEO 279 - week/year

GUIDE TO USE

- Cabling rules are given in EN 50343 and EN 50355
- Permissible current carrying capacities: values and calculation method are given in EN 50343
- Bending radius:
 - Static use: 4 x outer cable diameter
 - For installation and occasional movements: 6 x outer cable diameter
- Pulling tensible force (dynamic) during installation: 50 N/mm² of copper size
- Mechanical static tensible force: 15N/mm² of copper size



导线柔软度
超柔软等级6



无卤
EN 60754-1 & EN 60684-2



额定电压U₀/U
1.8 / 3 (3.6) kV



阻燃 - 火焰
EN 60332-1-2



阻燃
EN IEC 60332-3-24
(cat. C); EN IEC 60332-3-25
(EN50305)



烟密度
EN/IEC 61034-2



气体毒性
EN 50305-9.2



操作温度
-50 ... 120 ° C

CHARACTERISTICS

结构特性

导体材料	裸铜
导线柔软度	超柔软等级6
绝缘	High temperature silicone
无卤	EN 60754-1 & EN 60684-2

尺寸特性

导线截面	95 mm ²
导线直径	12.5 mm
标称外径	18.3 mm
外径最小值	17.0 mm
Maximum outer diameter	19.9 mm
近似重量	973 kg/km

电气特性

额定电压U ₀ /U	1.8 / 3 (3.6) kV
-----------------------	------------------

使用特性

阻燃 - 火焰	EN 60332-1-2
阻燃	EN IEC 60332-3-24 (cat C); EN IEC 60332-3-25 (EN50305)
烟密度	EN/IEC 61034-2
气体毒性	EN 50305-9.2
操作温度范围	-50 ... 120 ° C
芯线最高静止温度	150 ° C
Overload maximum core temperature	170 ° C
耐化学物质	好