

Reference: 10265265  
EAN 13: 3427580726538

#### CONTACT

Market information  
industryprojects.business@lynx<sup>eo</sup>  
ogroup.com

## Fire Resistant Armoured cables CR1-C1-C2 RATP Specification K27

### STANDARDS

**Product** IEC 60228; NF C32-310

**Test** NF C32-070/C1; NF C32-070/C2

### FIRE PERFORMANCE

- Flame retardant: According to RATP K20 specification
- Fire retardant : According to RATP K20 specification
- Fire resistant : According to RATP K20 specification
- Low smoke: According to RATP K20 specification
- Without Halogene: According to RATP K20 specification
- Low Toxicity: According to RATP K20 specification
- Low Corrosivity: According to RATP K20 specification

### DESIGN

- **Conductor:** Bare copper - Solid class 1 for cross section < 4mm<sup>2</sup> - Stranded class 2 for cross section ≥ 4mm<sup>2</sup>
- **Insulation :** Mica tape + Silicone rubber
- **Inner sheath:** Halogen free Polyolefin
- **Armour:** Stainless steel tapes for single core, steel tapes for multicores
- **Outer sheath:** Halogen free Polyolefin, Colour : orange

### Core identification

1x: White  
2x: blue-brown  
3x: brown-black-grey (brown-black-blue for cross sections 1,5mm<sup>2</sup> and 2,5mm<sup>2</sup>)  
3G: green/yellow-blue-brown  
4x: blue-brown-black-grey  
4G: green/yellow-brown-black-grey  
5x: blue-brown-black-grey-black  
5G: green/yellow-blue-brown-black-grey  
7x: white numbered with or without green/yellow

### Marking

K27 - 600/1000 - Nber of cores & cross-section - ARME - MM/YY - LYNXEO 279 - Manufacturing n° + metric marking



Halogen free  
IEC 60754-1



Mechanical  
resistance to  
impacts  
Good



Fire resistant  
NF C 32-070 CR1



Fire retardant  
NFC 32070 C1



Flame retardant  
NFC 32070 C2



Smoke density  
IEC 61034-2



Gases corrosivity  
IEC 60754-2



Operating temp.  
-20 ... 70 °C

**CHARACTERISTICS****Construction characteristics**

Conductor material	Plain copper
Type of conductor	Stranded, class 2
Insulation	Mica tape
Insulating material	Silicone
Inner sheath	Polyolefin
Armour type	Steel tapes
Outer sheath	Halogen free polyolefin
Sheath colour	Orange
Halogen free	IEC 60754-1
With Green/Yellow core	No

**Dimensional characteristics**

Number of cores	1
Conductor cross-section	95 mm <sup>2</sup>
Maximum outer diameter	27.0 mm
Approximate weight	1493 kg/km
Minimum outer diameter	- mm

**Electrical characteristics**

DC permissible current rating	- A
Voltage Drop	- V/A.km

**Mechanical characteristics**

Mechanical resistance to impacts	Good
----------------------------------	------

**Usage characteristics**

Fire resistant	NF C 32-070 CR1
Fire retardant	NFC 32070 C1
Flame retardant	NFC 32070 C2
Smoke density	IEC 61034-2
Gases corrosivity	IEC 60754-2
Operating temperature, range	-20 ... 70 °C
Max. conductor temperature in service	90 °C
Oil resistance	Good
Chemical resistance	Good
Rodent protection	Yes