



**Reference:** 10270789  
**EAN 13:** 3427580734427

### FIRE PERFORMANCE CLASS



B2ca-s1a,d0,a1

### CONTACT

Market information  
industryprojects.business@lynx  
ogroup.com

These cables are intended for fixed power or lighting circuits in tunnels, stations and subway stations. These B2ca cables comply with RATP K20 specifications .

### STANDARDS

**Product** EN 50575; EN 60228

**Installation** NF F 55-625

### APPLICATION

These cables are used for fixed power or lighting installations in tunnels and underground stations.

### FIRE PERFORMANCE

- Flame retardant: according to RATP K20 specification
- Fire retardant: according to RATP K20 specification
- Low smoke: according to RATP K20 specification
- Low toxicity: According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification
- Without Halogen : According to RATP K20 specification

**Reaction to fire: B2ca-s1a, d0, a1**

### DESIGN

- **Conductor:** Bare copper class 1 or 2
- **Insulation:** Cross-linked Polyethylene (XLPE)
- **Assembling:** An inner sheath acting as a filler
- **Outer sheath:** Polyolefin without halogen Colour : black

### Core identification

According to NF F 55625

2x: black - blue

3x: black - grey - brown

3G: black - blue - green/yellow

4x: black - blue - brown - black

4G: black - blue - brown - green/yellow

5G: black - blue - brown - black - green/yellow

≥ 7 conductors: black cores printed with numbers with or without green/yellow



Senza alogeno  
IEC/EN 60754-1



Ritardante la fiamma  
IEC/EN 60332-1-2



Densita' fumo  
IEC 61034-2 & EN 61034-2



Fumo  
IEC/EN 60754-2



Temp. max di servizio del conduttore  
90 °C



Temperatura Operativa  
-20 ... 60 °C

**CHARACTERISTICS****Caratteristiche costruttive**

Tipo di conduttore	A trefoli, Classe 2
Materiale del conduttore	Rame nudo
Isolamento	XLPE (polietilene reticolato)
Guaina esterna	Poliolfina senza alogeni
Senza alogeno	IEC/EN 60754-1
Con anima giallo/verde (terra)	N

**Caratteristiche dimensionali**

Numero di anime	2
Sezione del conduttore del cavo	2,5 mm <sup>2</sup>
Diametro esterno min	- mm
Diametro esterno max	12,6 mm
Peso approssimativo del cavo	210 kg/km

**Caratteristiche d'utilizzo**

Ritardante la fiamma	IEC/EN 60332-1-2
Densita' fumo	IEC 61034-2 & EN 61034-2
Fumo	IEC/EN 60754-2
Temperatura massima di servizio del conduttore	90 °C
Temperatura Operativa	-20 ... 60 °C

**COMPLEMENT****Bending radius**

$r = 8 \times \text{maximum outer diameter}$

**SELLING AND DELIVERY INFORMATION****Marking**

750 V cables: 750 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking  
 1000 V cables: 1000 - Nber of cores & cross-section - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000648-FRME + metric marking