



Reference: 10270798
EAN 13: 3427580734519

FIRE PERFORMANCE CLASS



B2ca-s1a,d0,a1

CONTACT

Market information
industryprojects.business@lynxegroup.com

STANDARDS

Product EN 50575; EN 60228

Installation NF F 55-625

APPLICATION

These cables are used for fixed power or lighting installations in tunnels and underground stations.

FIRE PERFORMANCE

- Flame retardant: according to RATP K20 specification
- Fire retardant: according to RATP K20 specification
- Low smoke: according to RATP K20 specification
- Low toxicity: According to RATP K20 specification
- Low corrosivity: According to RATP K20 specification
- Without Halogen : According to RATP K20 specification

Reaction to fire: B2ca-s1a, d0, a1

DESIGN

- **Conductor:** Bare copper class 5
- **Insulation:** Cross-linked Polyethylene (XLPE)
- **Assembling:** An inner sheath acting as a filler
- **Outer sheath:** Polyolefin without halogen. Colour: black

Core identification

According to NF F 55625

2x: black - blue

3x: black - grey - brown

3G: black - blue - green/yellow

4x: black - blue - brown - black

4G: black - blue - brown - green/yellow

5G: black - blue - brown - black - green/yellow

≥ 7 conductors: black cores printed with numbers with or without green/yellow



Senza alogeno
IEC/EN 60754-1



Ritardante la fiamma
IEC/EN 60332-1-2



Densita' fumo
IEC 61034-2 & EN 61034-2



Fumo
IEC/EN 60754-2



Temp. max di servizio del conduttore
90 °C



Temperatura Operativa
-20 ... 60 °C

CHARACTERISTICS

Caratteristiche costruttive

Tipo di conduttore	Flessibile classe 5
Materiale del conduttore	Rame nudo
Isolamento	XLPE (polietilene reticolato)
Guaina esterna	Poliolefina senza alogeni
Senza alogeno	IEC/EN 60754-1
Con anima giallo/verde (terra)	N

Caratteristiche dimensionali

Numero di anime	2
Sezione del conduttore del cavo	1,5 mm ²
Diametro esterno max	11,5 mm
Peso approssimativo del cavo	161 kg/km

Caratteristiche d'utilizzo

Ritardante la fiamma	IEC/EN 60332-1-2
Densita' fumo	IEC 61034-2 & EN 61034-2
Fumo	IEC/EN 60754-2
Temperatura massima di servizio del conduttore	90 °C
Temperatura Operativa	-20 ... 60 °C

COMPLEMENT

Bending Radius

$r = 6 \times \text{maximum outer diameter}$

SELLING AND DELIVERY INFORMATION

Marking

750 V cables : 750 - Nber of cores & cross-section - S - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000148-FRME + metric marking

1000 V cables : 1000 - Nber of cores & cross-section - S - SH - NF F 55-625 - LYNXEO 279 - WW - YY - B2ca-s1a, d0, a1 - Manufacturing number DoP:1000148-FRME + metric marking



Senza alogeno
IEC/EN 60754-1



Ritardante la fiamma
IEC/EN 60332-1-2



Densita' fumo
IEC 61034-2 & EN 61034-2



Fumo
IEC/EN 60754-2



Temp. max di servizio del conduttore
90 °C



Temperatura Operativa
-20 ... 60 °C