



Reference: 10272430
EAN 13: 3427580736575

CONTACT

Markets and Products Information
 rollingstock.business@lynxgroup.com

- CST 74C068
- Quality insurance according to RCC-E
- Zero halogen (SH)
- Control cables 0.3/0.5(0.6)kV
- **Cables installed inside of the containment area (K1)**
- Without Screen (SE)
- Unarmoured (NA)

STANDARDS

Product IEC 60228

Test a; IEC 60332-3-23; IEC 60754-1; IEC 61034-2; NF C32-070/C1

APPLICATIONS

These control cables allow connection to a variety of industrial equipment from control room.

DESIGN

Conductor:

- Stranded (class 2) or flexible (class 5) plain copper

Insulation:

- Zero halogen (SH), cross-linked

Assembling:

- Polyester tape (optional)

Outer sheath:

- Low smoke, zero halogen (LSZH)
- Colour: Grey

Core identification

Black cores printed with white numbers
 Optional: with G/Y core

Marking

LYNXEO 279 Nber of cores & cross-section Cu CST 74 C 068 K1 SH 0.3/0.5(0.6) kV YYYY Manufacturing number + metric marking



Halogen free
 IEC 60754-1; IEC 60754-2



Rated Voltage U_o/U_m
 (Um)
 0.3/0.5(0.6)kV



Operating temp.
 -20 ... 60 °C



Smoke density
 IEC 61034-2



Fire retardant
 NF C 32070 C1;
 IEC 60332-3-24
 (cat.B)



Life cycle 60years
 Yes



U.V resistance
 Yes



Radiation resistant
 Yes

CHARACTERISTICS

Construction characteristics

Conductor material	Plain copper
Type of conductor	Flexible, Classe 5
Insulation	Halogen-free
Outer sheath	LSZH
Halogen free	IEC 60754-1; IEC 60754-2

Dimensional characteristics

Conductor cross-section	1.5 mm ²
Number of cores	3
Conductor diameter	1.5 mm
Diameter over insulation	2.7 mm
Minimum outer diameter	8.8 mm
Maximum outer diameter	10.1 mm
Approximate weight	135 kg/km

Electrical characteristics

Max. DC resistance of the conductor at 20°C	13.3 Ohm/km
Maximum DC resistance of the conductor at 90°C	16.900 Ohm/km
Reactance at 50 Hz	0.098 Ohm/km
Short Circuit Current 0,3 s Max	0.39 kA
Short Circuit Current 1 s Max	0.21 kA
Voltage Drop	27.2 V/A.km
Impedance at 50 Hz	13.3 Ohm
Calorific Power	1.8 MJ/m
Rated Voltage U _o /U (U _m)	0.3/0.5(0.6)kV

Usage characteristics

Operating temperature, range	-20 ... 60 °C
Smoke density	IEC 61034-2
Fire retardant	NF C 32070 C1; IEC 60332-3-24 (cat.B)
Life cycle 60years	Yes
U.V resistance	Yes
Radiation resistant	Yes
Loss of coolant accident resistant	Yes
Max. conductor temperature in service	90 °C
Nuclear Classification	Class 1 E LOCA /K1

SELLING AND DELIVERY INFORMATION

Minimum bending radius:

10 x outer diameter
To be doubled during laying operations