



Reference: 10282799

CONTACT

Market information
 industryprojects.business@lynxgroup.com

International Designation: MPRX 331 0.6/1KV 2X4

FIRE RESISTANT POWER CABLES

STANDARDS

Product IEC 60228

Installation IEC 60092-350; IEC 60092-353; IEC 60092-360

Test a; IEC 60331-1 or 2; IEC 60332-1; IEC 60332-3-22; IEC 60754-1; IEC 61034

APPLICATION

MPRX®331 0.6/1 kV fire resistant power and control cables maintain circuit integrity in case of fire by meeting performances requirements from the IEC 60331 series for 180 minutes. They are used for detection and warning systems not subject to mechanical risks.

The highly flexible MPRX®331 FLEXISHIP® range is recommended for installations and connections in narrow spaces where an optimal bending radius is required. Designed with halogen-free fire retardant materials, they provide optimum safety for people and maximal asset protection against all risks of fire.

Design

1. Conductor

Stranded bare copper, class 2 or class 5 for FLEXISHIP®

2. Insulation

Mica tape + XLPE (cross-linked polyethylene)

3. Outer sheath

(Filler if necessary)
 Polyolefin SHF1
 Colour: orange

Example of marking:

LYNXEO 279 MPRX 331 or MPRX 331 FLEXISHIP 0.6/1 kV "n" x (orG) "s" 90°C IEC 60092-353 IEC 60332-3-22 Cat. A IEC 60331-1/21 "ww/yy" * CE* + metric marking

Core Identification

1 x: black

2 x: brown-blue

3 x: brown-black-grey

3G: brown-blue-green/yellow

4 x: brown-black-grey-blue

4G: brown-black-grey-green/yellow

> 5 cores: n x: white with printed numbers / nG: white with printed numbers + green/yellow core



Halogen free
 IEC 60754-1



Conductor flexibility
 Stranded class 5



Rated Voltage Uo/U
 (Um)
 0.6/1 (1.2) kV



Fire resistant
 IEC 60331-1 or -2



Fire retardant
 EN IEC 60332-3-22
 (cat A)



Smoke density
 IEC 61034



Gases corrosivity
 IEC 60754-2



Operating temp.
 -30 ... 80 °C

CHARACTERISTICS

Construction characteristics

| | |
|-----------------------------------|---------------------|
| Conductor material | Bare copper |
| Halogen free | IEC 60754-1 |
| Sheath colour | Orange |
| Insulation | XLPE + Mica tape |
| Material of filler / inner sheath | Filler if necessary |
| Outer sheath | Polyolefin |
| Conductor flexibility | Stranded class 5 |
| With Green/Yellow core | No |

Dimensional characteristics

| | |
|-------------------------|-------------------|
| Number of cores | 2 |
| Conductor cross-section | 4 mm ² |
| Minimum outer diameter | 11.6 mm |
| Maximum outer diameter | 13.3 mm |
| Approximate weight | 156 kg/km |
| Nominal outer diameter | 12.4 mm |

Electrical characteristics

| | |
|---|-----------------|
| Rated Voltage U ₀ /U (U _m) | 0.6/ 1 (1.2) kV |
| Permissible short circuit current | 0.6 kA |
| Permissible current rating in open air | 34 A |
| Max. DC resistance of the conductor at 20°C | 4.61 Ohm/km |

Usage characteristics

| | |
|---------------------------------------|---------------------------|
| Fire resistant | IEC 60331-1 or -2 |
| Fire retardant | EN IEC 60332-3-22 (cat A) |
| Smoke density | IEC 61034 |
| Gases corrosivity | IEC 60754-2 |
| Operating temperature, range | -30 ... 80 °C |
| Max. conductor temperature in service | 90 °C |

OTHER CHARACTERISTICS

Test Voltage

AC between cores..... 3.5 kV AC

Minimum bending radius for fixed installations

- MPRX® 331..... 6 x outer diameter
- MPRX® 331 FLEXISHIP®..... 5 x outer diameter